NAVAL POSTGRADUATE SCHOOL
Monterey, California

THESIS

A SIMPLIFIED SCHEME
TO PERFORM PRICE ADJUSTING SAMPLING
FOR QUALITY ASSURANCE

by

William Paul Keane

September 1980

Thesis Advisor: Glenn F. Lindsay

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO. AD·A093625	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A Simplified Scheme to Perform Price Adjusting Sampling for Quality Assurance,		5. TYPE OF REPORT & PERIOD COVERED Master's Thesis; September 1980
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) William Paul Keane		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93941		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California 93941		12. REPORT DATE September 1980
		13. NUMBER OF PAGES 65 pages
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office) Naval Postgraduate School Monterey, California 93941		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Quality assurance, sampling methods, price adjusting sampling

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

This thesis presents a quality assurance scheme which eliminates the necessity of rejecting lots. The mechanism used to motivate suppliers to provide lots at an acceptable quality level is to adjust the price paid for the lot based on the results of a sample. Information contained in Military Standard 105D and a concept referred to as Price Adjusted Single Sampling are combined in order to develop a system which allows a decision maker to find a sampling plan by selecting three parameters.

DD FORM 1473 EDITION OF 1 NOV 68 IS OBSOLETE
(Page 1) S/N 0102-014-6601

A Simplified Scheme
to Perform Price Adjusting Sampling
for Quality Assurance

by

William Paul Keane
Lieutenant, Civil Engineer Corps
United States Navy
B.S., University of Notre Dame, 1969

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN OPERATIONS RESEARCH

from the

NAVAL POSTGRADUATE SCHOOL
September 1980

Author: _____

Approved by: _____
                                        Thesis Advisor

             _____
                                        Second Reader

             _____
             Chairman, Department of Operations Research

             _____
             Dean of Information and Policy Sciences

2

ABSTRACT

This thesis presents a quality assurance scheme which eliminates the necessity of rejecting lots. The mechanism used to motivate suppliers to provide lots at an acceptable quality level is to adjust the price paid for the lot based on the results of a sample. Information contained in Military Standard 105D and a concept referred to as Price Adjusted Single Sampling are combined in order to develop a system which allows a decision maker to find a sampling plan by selecting three parameters.

TABLE OF CONTENTS

I. INTRODUCTION

The traditional method of specifying an acceptance sampling plan for quality assurance has been to identify the number of items to be inspected, which is referred to as the sample size, and the acceptance number. The acceptance number is defined as the maximum number of unsatisfactory items in the sample which still allows the entire group of items, or lot, to be accepted. If the results of the sampling process indicate that the lot is acceptable, a predetermined fixed price is paid to the supplier for the entire lot. If the lot is judged unacceptable, and therefore rejected, it is returned to the supplier without payment. There are instances, however, when rejecting a lot is not feasible. This thesis examines an alternative method of using the results of the sampling process to determine a variable price to be paid for a lot in consideration for each lot being accepted.

As a result of direction from the Office of Management and Budget, OMB Circular No. A-76 [8], agencies of the federal government have begun preparing for an increase in the amount of commercial and industrial services being performed by private contractors. Many of the services to be contracted are required on a regular basis, such as

janitorial work or bus service. For a service the term
item is defined as a scope of work or task. For example,
in janitorial work a trash basket is emptied or not emptied,
a floor is waxed as required or it is not, or in general,
the task is accomplished in a satisfactory or unsatisfactory
manner. For bus service an item could be a scheduled stop
which would be satisfactory if made within required time
limits. Using this definition of an item, the term _lot_ is
defined as the number of items which the customer expects
to receive over a given period of time, e.g., the number of
emptied trash baskets or the number of scheduled stops in a
month. From a practical viewpoint, unacceptable lots of
this kind cannot be rejected and returned to the contractor.
Military Standard 105D furnishes a wide range of sampling
plans for general use; however, in this context the standard
does not appear to be adequate or appropriate. An alterna-
tive sampling scheme directed towards determining how much
to pay for a lot needs to be developed. A possible scheme
will be presented in this paper.

In the next chapter we will develop the idea of expected
price paid per satisfactory item and examine the relation-
ship of this price to sampling plans in Military Standard
105D.

Price Adjusted Single Sampling (PASS) was originally in-
troduced by Joseph Foster [4] and subsequently developed by

Foster and Oscar Perry [5] and [6]. It is a generalized procedure to find a sampling plan consisting of a sample size and a formula to compute payments based on the number of unacceptable items found. In Chapter 3 the mathematics of this procecure will be reviewed in detail with particular attention being given to those items critical to the development of the proposed sampling scheme.

In later chapters equations necessary to create a simplified sampling scheme are developed. Then using an arbitrary set of parameters and attempting to duplicate the simplicity of the Military Standard, a model scheme is constructed. A discussion of the sensitivity of the scheme to changes in the parameters is followed by a set of recommendations for further study.

II. EXPECTED COST PER SATISFACTORY ITEM

Expected cost per satisfactory item, $C(p)$, is an important idea utilized in creating the sampling scheme presented in this paper. After a brief review of Military Standard 105D, it will be shown that Military Standard 105D exhibits an interesting relationship between $C(p)$ and acceptable quality level, AQL.

A. MILITARY STANDARD 105D

Military Standard 105D has been a widely used set of sampling plans since being issued in 1963. In order to use Military Standard 105D, it is necessary to know lot size, N, and to have designated an "acceptable quality level," or AQL. The AQL is set by the customer and is defined as the percent of defective items (in a lot) which the customer considers acceptable. Under plans from Military Standard 105D, lots having AQL quality will be accepted with a high probability. It is also necessary to decide on an "inspection level" which determines the relationship between lot size and sample size.

Although Military Standard 105D provides sets of double and multiple sampling plans, we shall be primarily concerned with single sampling. Each single sampling plan in the standard provides a sample size, n, and an acceptance

number, A_c, depending on the type of inspection in effect, either normal, tightened, or reduced. Criteria are provided in the plan to shift from one type of inspection to another, depending on the experience with previously inspected lots. These shifts will result in the values of A_c and/or n being changed.

It has been stated that "Military Standard 105D plans are not based upon cost concepts" [1]. This is, at least, an arguable point since the rules for using the standard allow the consumer to adjust the amount of sampling done per lot in relation to lot size by choosing a level of inspection consistent with cost considerations. However, by another criterion, Military Standard 105D does involve cost, i.e., expected cost per satisfactory item.

B. EXPECTED COST PER SATISFACTORY ITEM

Expected cost per satisfactory item, $C(p)$, is defined as follows:

$$C(p) = \frac{\text{Pr (accept lot}|p)NC'}{N(1-p)} = \frac{P_a C'}{1-p} . \qquad (1)$$

Here C' is the contracted price paid for each item in an accepted lot.

To illustrate the relationship between $C(p)$ and p, data was taken from the table for normal inspection contained in Military Standard 105D. The AQL's 1.0, 1.5, 2.5, 4.0, 6.5, and 10.0 were chosen as the area of interest. In order to

use available tables of cumulative binomial probabilities [7], sample size was restricted to 50, 80, and 125. Using these tables to determine the probability of acceptance, P_a, for a given p, inserting the results into Equation (1), and letting C' equal 1.0 led to the values shown in Table I.

As can be seen, the value of p which tends to maximize C(p) is the AQL. This behavior becomes more evident as AQL increases and as sample size increases.

Since it could be argued that normal inspection is only part of the overall sampling scheme set forth in Military Standard 105D, an analysis was done to determine if shifting among normal, tightened and reduced inspection would have similar results. In order to do this, tables contained in a paper by Gerald Brown and Herbert Rutemiller [1] were used. These tables yield an acceptance probability, P_a, based on AQL, p and n, which accounts for shifts between types of inspection. For the current investigation values of n were restricted to the three largest available in the Brown paper for each given AQL. Again letting C' equal 1.0 and using Equation (1), the values in Table II were computed.

As can be seen by comparing Tables I and II, the results are consistent in that C(p) is maximized at the AQL. It does not seem likely that this result was an objective when the standard was developed but, rather, is

10

a fortunate byproduct. It is intuitively appealing that suppliers should be encouraged to provide lots close to AQL quality. This suggests that a sampling scheme could be developed which uses the idea of maximizing $C(p)$ at the AQL.

TABLE I

C(p), Relationship Between Expected Price Per Satisfactory Item, and Incoming Percent Defective, p, Using Military Standard 105D, Normal Inspection

	AQL 1.0%				AQL 1.5%		
	p	P_a	C(p)		p	P_a	C(p)
n = 50				n = 50			
	0	100.	1.0		0	100.	1.0
	.3	99.	.993		1.0	98.6	.996
	1.0	91.1	.920		1.7	95.0	.966
	2.0	73.6	.751		2.0	92.2	.941
					3.0	81.1	.836
n = 80				n = 80			
	0	100.	1.0		0	100.	1.0
	.6	99.	.996		2.0	100.	1.020
	1.0	95.3	.963		3.0	99.9	1.030
	2.0	78.4	.800		4.0	98.8	1.029
					5.0	95.1	1.001
					6.0	86.9	.924
n = 125				n = 125			
	0	100.	1.0		0	100.	1.0
	.7	99.	.997		1.0	99.8	1.01
	1.0	96.3	.973		1.4	99.0	1.004
	2.0	75.9	.774		2.0	96.0	.980
					3.0	86.6	.850

TABLE I (Continued)

	AQL 2.5%				AQL 4.0%		
	p	P_a	C(p)		p	P_a	C(p)
n = 50				n = 50			
	1.0	99.9	1.009		3.0	99.6	1.027
	1.7	99.0	1.007		3.7	99.	1.028
	2.0	98.2	1.002		4.0	98.6	1.027
	3.0	93.7	.966		5.0	96.2	1.013
	4.0	86.1	.897		6.0	92.2	.981
n = 80				n = 80			
	1.0	100	1.010		3.0	99.7	1.028
	2.0	99.5	1.015		3.7	99.0	1.028
	2.3	99.0	1.013		4.0	98.5	1.026
	3.0	96.7	.997		5.0	95.3	1.003
	4.0	89.9	.936		6.0	89.3	.950
n = 125				n = 125			
	1.0	100	1.010		2.0	100.	1.026
	2.0	99.6	1.016		3.0	99.9	1.030
	2.3	99.0	1.013		4.0	98.8	1.029
	3.0	96.5	.995		5.0	95.1	1.001
	4.0	87.1	.907		6.0	86.9	.924

TABLE I (Continued)

	AQL 6.5%				AQL 10.0%		
	p	P_a	C(p)		p	P_a	C(p)
n = 50				n = 50			
	5.0	99.7	1.049		8.0	99.8	1.085
	6.0	99.1	1.054		9.0	99.6	1.095
	7.0	98.6	1.052		10.0	99.1	1.101
	8.0	97.8	1.039		11.0	98.2	1.103
	9.0	95.6	1.014		12.0	96.8	1.100
n = 80				n = 80			
	4.0	100	1.041		8.0	99.8	1.085
	5.0	99.8	1.051		9.0	99.5	1.093
	6.0	99.2	1.055		10.0	98.8	1.099
	7.0	97.7	1.051		11.0	97.3	1.093
	8.0	94.6	1.028		12.0	94.8	1.073
n = 125				n = 125			
	4.0	100	1.041		8.0	100	1.087
	5.0	99.8	1.051		9.0	99.8	1.097
	6.0	99.2	1.055		10.0	99.4	1.104
	7.0	97.2	1.045		11.0	98.2	1.104
	8.0	92.5	1.005		12.0	95.8	1.088

14

TABLE II

Relationship Between Expected Price Per Satisfactory Item, C(p) and Incoming Percent Defective p, Using Military Standard 105D and Shifting Types of Inspection

	AQL 1.0%				AQL 1.5%		
	p	P_a	C(p)		p	P_a	C(p)
n = 50				**n = 50**			
	.25	99.7	.999		.375	100.	1.004
	.50	98.2	.987		.750	99.9	1.007
	.75	95.3	.960		1.125	99.0	1.001
	1.0	90.5	.914		1.5	96.5	.980
	1.25	84.3	.854		1.875	92.0	.934
n = 80				**n = 80**			
	.25	100.	1.003		.375	100.	1.004
	.50	99.8	1.003		.75	99.9	1.007
	.75	99.0	.997		1.125	99.1	1.002
	1.0	96.1	.971		1.5	96.9	.984
	1.25	90.6	.917		1.875	92.6	.944
n = 125				**n = 125**			
	.25	100.	1.003		.375	100.	1.004
	.50	99.9	1.004		.75	100.	1.007
	.75	99.0	1.007		1.125	99.8	1.009
	1.0	96.3	.973		1.5	98.9	1.004
	1.25	91.4	.926		1.875	96.4	.982

15

TABLE II (Continued)

AQL 2.5%				AQL 4.0%		
p	P_a	C(p)		p	P_a	C(p)
n = 50				n = 32		
.625	100.	1.006		2.0	99.9	1.019
1.25	99.9	1.012		3.0	99.	1.021
1.875	99.	1.009		4.0	96.2	1.002
2.5	96.3	.985		5.0	91.8	.956
3.125	91.4	.943		6.0	82.9	.882
n = 80				n = 50		
.625	100.	1.006		2.0	100.	1.020
1.25	100.	1.013		3.0	99.8	1.029
1.875	99.8	1.017		4.0	98.5	1.026
2.5	98.5	1.010		5.0	95.0	1.000
3.125	95.0	.981		6.0	87.7	.933
n = 125				n = 80		
.625	100.	1.006		2.0	100.	1.020
1.25	100.	1.013		3.0	99.8	1.029
1.875	99.9	1.018		4.0	98.5	1.026
2.5	98.6	1.011		5.0	94.0	.989
3.125	92.7	.957		6.0	83.5	.888

TABLE II (Continued)

AQL 6.5%				AQL 10.0%		
p	P_a	C(p)		p	P_a	C(p)
n = 20			n = 13			
3.25	99.9	1.033		5.0	99.9	1.052
4.875	98.9	1.040		7.5	98.2	1.068
6.5	95.9	1.026		10.0	95.7	1.063
8.125	91.3	.983		12.5	90.1	1.030
9.75	82.1	.910		15.0	82.0	.965
n = 32			n = 20			
3.25	100.	1.034		5.0	100.	1.052
4.875	99.7	1.048		7.5	99.8	1.079
6.5	98.1	1.049		10.0	98.5	1.094
8.125	93.9	1.022		12.5	95.0	1.086
9.75	85.8	.944		15.0	87.7	1.032
n = 50			n = 32			
3.25	100.	1.034		5.0	100.	1.052
4.875	99.8	1.049		7.5	99.8	1.079
6.5	98.4	1.052		10.0	98.4	1.093
8.125	93.4	1.017		12.5	94.0	1.074
9.75	82.2	.911		15.0	83.5	.982

III. PRICE ADJUSTED SINGLE SAMPLING

One of the purposes of an acceptance sampling program
is to motivate the supplier to provide lots possessing at
least an acceptable level of quality. This can be done by
rejecting lots of apparent poor quality, which increase the
supplier's costs, or, as done in Price Adjusted Single
Sampling (PASS), by adjusting contract price, which reduces
the supplier's receipts.

The underlying concept of price adjusted sampling plans
is "economic indifference." In developing his idea of
acceptance sampling plans with price differentials [9],
Robert Roeloffs recognized this when he stated that "the
consumer may be willing to pay a higher price for a product
with a lower proportion defective." Roeloffs did not,
however, pursue this idea explicitely. Foster and Perry
introduced their sampling system using a linear indifference
function, subsequently expanding PASS to include a quadratic
indifference function, dependent on quality level p. The
function is defined as

$$h(p) = NC(A_o + A_1 p + A_2 p^2). \tag{2}$$

The constants N and C are defined, respectively, as the lot
size and the average price per acceptable unit the consumer
is willing to pay. Restrictions on the coefficients A_o,
A_1, and A_2 will be discussed in Chapter IV.

18

A. STATISTICAL DEVELOPMENT OF PASS

Let us consider a sample of size n drawn from a lot of N items. The number of defective items in a sample is denoted by x. Since the sample is taken without replacement, the random variable X which represents the number of defective items found is hypergeometrically distributed. It is assumed that N is much larger than n so the binomial approximation to the hypergeometric can be used.

To develop a PASS plan, it is necessary to identify a relationship between the total lot price P_t and x, the number of defective items in the sample. Let

$$P_t = N(C - g(x)) , \qquad (3)$$

where g(x) is a function of the number of defective items. In order that P_t decreases as x increases, g(x) must be monotone increasing. In Equation (3), P_t represents the actual amount paid for a lot, while in Equation (1), h(p) represents what the consumer is willing to pay for a lot if the quality level p is known. Since the consumer wants to pay in the long run an average amount equal to what he is willing to pay, the expected value of the total lot price is equated to h(p),

$$E[P_t] = E[N(C - g(x))] = h(p). \qquad (4)$$

Substituting Equation (2),

$$E[N(C - g(x))] = N\,C\,(A_0 + A_1\,p + A_2p^2),$$

and $NC - NE[g(x)] = NC(A_0 + A_1\,p + A_2p^2),$

and thus:

$$E[g(x)] = C\,(1 - A_0 + A_1\,p + A_2p^2). \qquad (5)$$

In order to use all the information contained in the coefficients of the indifference functions, let

$$g(x) = B_0 + B_1\,x + B_2\,x^2. \qquad (6)$$

Then $E[g(x)] = B_0 + B_1\,E(x) + B_2\,E(x^2).$
Since it has been assumed that the binomial approximation applies,

$$E[g(x)] = B_0 + B_1np + B_2[np(1-p) + (np)^2]. \qquad (7)$$

Equating Equations (5) and (7) and combining terms, we have:

$$C(1-A_0) - CA_1p - CA_2p^2 = B_0 + (B_1 + B_2)\,np + B_2n\,(n-1)p^2.$$

Equating coefficients of p yields:

$$B_0 = C(1 - A_0),$$

$$B_1 = \frac{CA_2 - CA_1(n-1)}{n(n-1)},$$

$$B_2 = \frac{CA_2}{n(1-n)}.$$

Substituting Equation (6) into Equation (3) and using the above relationships, P_t becomes:

20

$$P_t = NC \left[1 - \left(1 - A_0 + \frac{A_2 x}{n(n-1)} - \frac{A_1(n-1)x}{n(n-1)} + \frac{A_2 x^2}{n(1-n)}\right) \right],$$

$$\text{or} \quad P_t = NC \left(A_0 + \frac{A_1 x}{n} - \frac{A_2 x}{n(n-1)} + \frac{A_2 x^2}{n(n-1)}\right) = NCQ(x) \qquad (8)$$

This is the final formula for computing payments.

In order to completely specify the plan, sample size, n, must be known. To find n it is necessary to define a PASS relationship involving producer's or consumer's risk.

B. PRODUCER'S AND CONSUMER'S RISK

Foster and Perry define the relationship involving producer's risk as follows: If the fraction defective is some predetermined quality level p, then the probability that the price paid per nondefective item is less than or equal to a specified lower bound, L, should be less than or equal to a predetermined probability, α. That is,

$$\Pr\left\{ \text{Price per nondefective item} \leq L \mid p = p_1 \right\} \leq \alpha. \qquad (9)$$

The predetermined probability of being paid less than a specified lower bound α is the producer's risk. This definition can be contrasted to that given by Acheson Duncan [2], who defines "producer's risk is the probability of rejection....It is usually used in reference to rejection of lots from a process the average quality of which equals the AQL."

The relationship involving consumer's risk, β, for some specified upper bound, U, can be written:

21

$$\Pr\left\{\text{Price per nondefective item} \geq U \mid p = p_2\right\} \leq \beta. \quad (10)$$

Consumer's risk is the probability that the consumer will pay more than a specified upper bound, U, if the lot quality is a specified fraction defective. Historically, consumer's risk has been defined as "the probability of accepting a lot the quality of which is equal to (a specified) fraction defective." [2]

In lieu of discussing producer or consumer risk, it is also possible to refer to producer or consumer protection. If producer's risk is the probability α that the price received will be less than some lower bound, L, then producer protection, $1-\alpha$, is the probability that the price will be greater than or equal to L. Consumer protection is similarly defined.

Equations (9) and (10) can be rewritten as follows:

$$\Pr\left\{\text{NCQ}(x) \leq \text{NL}(1-p_1)\right\} \leq \alpha,$$

or

$$\Pr\left\{Q(x) - \frac{L}{C}(1-p_1) \leq 0\right\} \leq \alpha, \quad (11)$$

and

$$\Pr\left\{Q(x) - \frac{U}{C}(1-p_2) \geq 0\right\} \leq \beta, \quad (12)$$

where

$$Q(x) = A + \frac{A_1 x}{n} - \frac{A_2 x}{n(n-1)} + \frac{A_2 x^2}{n(n-1)}.$$

The problem now is to find the minimum value of n which will result in either Equation (11) or (12) being satisfied, depending upon whether producer or consumer

protection is desired. Consider the case where $h(p)$ is concave, i.e., A_2 is negative. The procedure is one of successive approximation. Referring to Equation (11), if we fix n, we could find an x such that:

$$A + \frac{A_1 x}{n} - \frac{A_2 x}{n(n-1)} + \frac{A_2 x^2}{n(n-1)} - \frac{L}{C}(1-p_1) = 0. \qquad (13)$$

Let x_1 and x_2 be the roots of this equation: $x_1 \leq x_2$.

Here, $\Pr\left(Q(x) - \frac{L}{C}(1-p_1) \leq 0\right) \leq \alpha$ is equivalent to

$$\Pr(X \leq x_1) + \Pr(X \geq x_2) \leq \alpha. \qquad (14)$$

Similarly, referring to Equation (12) and assuming A_2 to be negative.

$$\Pr\left(Q(x) - \frac{U}{C}(1-p_2) \geq 0\right) = \Pr(x_1 \leq X \leq x_2) \leq \beta. \qquad (15)$$

To find the minimum sample size, the solution procedure is to assume an n, then solve for x_1 and x_2. Knowing n, x_1, and x_2, one may calculate the probability that the random variable X is in the region specified by Equation (14) or (15), whichever is applicable. We continue incrementing n until the probability of occurrence is less than or equal to the desired value.

Similar results can be obtained if $L(p)$ is convex. However, since the convex case does not allow the cost per satisfactory item to be maximized at a quality level other than zero, it is not considered further.

23

After the required sample size for PASS is established, and given that the indifference function is known, solving for the coefficients of the formula for computing payments, Equation (8), follows routinely. However, as Foster and Perry have pointed out, identifying the indifference function requires considerable effort, and finding the sample size requires a time consuming trial and error process. PASS could be much more useful if it could be converted into a set of tables in a format similar to Military Standard 105D.

IV. A MODEL FOR A PASS SCHEME

As stated previously, the process of developing an
indifference function h(p) can be time consuming. This
chapter will propose several ideas which, when combined,
simplify the selection of PASS coefficients A_0, A_1, and
A_2. Prior to doing this, however, a set of restrictions
on these coefficients will be identified.

A. RESTRICTIONS ON THE INDIFFERENCE FUNCTION COEFFICIENTS

In Chapter III we considered h(p) to be a concave
function, thus establishing the first restriction that A_2
be less than or equal to 0.

Recalling that $h(p) = NC(A_0 + A_1 p + A_2 p^2)$ represents
what the customer is willing to pay for a lot having known
quality p, it is unlikely that he would be willing to pay
more than NC if the percent defective were zero. It is
also unlikely that the supplier would accept less than NC
if p = 0. Therefore, the second restriction is that
$A_0 = 1.0$.

Another restriction on the coefficients can be traced
to the function $g(x) = \beta_0 + \beta_1 x + \beta_2 x^2$, which in terms of
the A_1's is

$$g(x) = P(1-A_0 + (\frac{A_2}{n-1} - A_1) \frac{x}{n} + \frac{A_2}{n(1-n)} x^2.$$

In order for g(x) to be monotone increasing, as required in Chapter III, A_1 must be less than or equal to 0.

Two other restrictions appear to be implicit in the indifference function itself. The value of h(p) should be less than or equal to 0 when p equals 1.0. Therefore, $A_1 + A_2$ must be less than or equal to -1.0. If we require that h(p) cannot be less than 0 if $p \leq 0.5$, then $A_2 + 2 A_1 \geq -4$. Table III summarizes these restrictions.

TABLE III

Restrictions on Indifference Curve Coefficients

1.) $A_2 \leq 0$ necessary

2.) $A_0 = 1$ not mandatory

3.) $A_1 \leq 0$ necessary

4.) $A_1 + A_2 \leq -1$ not mandatory

5.) $-4 \leq A_2 + 2 A_1$ not mandatory

It may be possible, on an individual case basis, to develop an indifference function having coefficients which violate these restrictions. Convex functions are an example. In this thesis, however, our subsequent work will deal only with functions which comply with the conditions shown in Table III.

B. THE PROPOSED MODEL

As stated in Chapter III, the first step in formulating a PASS plan is to identify the indifference function. When

26

a quadratic function is assumed, the problem then becomes one of identifying the coefficients A_0, A_1, and A_2. In the previous section it was noted that A_0 should be set equal to 1.0. Therefore, we might seek two equations in two unknowns which could be solved to determine A_1 and A_2. Recalling that $C(p)$ is defined as the expected price paid per satisfactory item, and using the relationships developed in the PASS system, we have

$$C(p) = E\left[\frac{P_t}{N(1-p)}\right] = \frac{E(P_t)}{N(1-p)} = \frac{h(p)}{N(1-p)}; \quad p \neq 1$$

or $\quad C(p) = \frac{C(1 + A_1 p + A_2 p^2)}{(1-p)}.$ $\qquad\qquad$ (16)

By taking the first derivative of Equation (16) and setting it equal to zero, a local extremum can be found. Thus

$$\frac{d(C(p))}{dp} = C\left(\frac{(1-p)(A_1 + 2A_2 p) + (1 + A_1 p + A_2 p^2)}{(1-p)^2}\right) = 0,$$

which implies that $1 + A_1 + A_2 (2p - p^2) = 0$.

Since the extremum (maximum price paid) should occur when p is equal to acceptable quality level, this equation becomes

$$1 + A_1 + A_2 (2\ AQL - AQL^2) = 0. \qquad\qquad (17)$$

Another equation which can be used is the indifference function. Let us consider the quality level $p = p_0$ to be

27

the level at which $h(p) = 0$, or $NC (1 + A_1 p_0 + A_2 p_0) = 0$

which gives $(1 + A_1 p_0 + A_2 p_0{}^2) = 0$. $\qquad$ (18)

Solving for A_1 in Equation (17) and inserting this into (18) yields $1 + p_0 (A_2 (AQL^2 - 2 AQL) -1) + A_2 p_0 = 0$,

or $\quad A_2 = \dfrac{p_0 - 1}{p_0 (AQL^2 - 2 AQL) + p_0{}^2}$, $\qquad$ (19)

and subsequently $A_1 = \dfrac{(1 - p_0) (2 AQL - AQL^2)}{p_0 (AQL^2 - 2 AQL) + p_0{}^2} - 1$. $\qquad$ (20)

It is now possible to create a table of A_1 and A_2 values for a given set of AQL's and P_0's. Such a table would permit one to determine A_1 and A_2 for specified values of the the acceptable quality level and the fraction defective at which the customer is unwilling to pay anything for the product received. For the purpose of developing a table using the proposed model, AQL's were chosen to be 0.03, 0.05, 0.08, 0.10, 0.15, 0.20, 0.25, and 0.30. Values for p_0 were taken to be 0.5, 0.6, 0.7, 0.8, 0.9, and 1.0. Using these values in Equations (19) and (2) resulted in Table IV.

These are two particularly interesting aspects of Table IV. The first is that when $p_0 = 1.0$, the values of the coefficients are not affected by changing the AQL. Thus, in order to meet the criteria for the model, the indifference function must be linear when $p_0 = 1.0$. A second observation is that the coefficients which would be in the

28

lower left corner of Table IV do not meet the restrictions
identified in Table III. Thus, these values cannot be used
and have been deleted. This leaves a set of AQL's and P_0's
excluded from the proposed sampling scheme. However, this
situation is not necessarily a problem, since the excluded
sets are those which would not be expected to be used. For
example, it is difficult to imagine a situation in which
a customer would be willing to pay the maximum price per non-
defective item at an AQL = .3 and at the same time specify
a p_0 = 0.5 at which he is unwilling to pay anything.

Having developed a set of coefficients for the indif-
ference function, the next stop is to consider sample size.
The next chapter will discuss the sensity of sample size
to PASS parameter changes in general and describe a method
to find a sample size for the set of indifference functions
whose coefficients are given in Table IV.

TABLE IV

Values for Indifference Function Coefficients A_1 and A_2

AQL[1]	p_0[2]	.5	.6	.7	.8	.9	1.0
.03	A_1	− .866	− .927	− .960	−.980	− .992	−1.000
	A_2	−2.208	−1.233	− .669	−.337	− .132	0
.05	A_1	− .758	− .871	− .931	−.965	− .987	−1.000
	A_2	−2.484	−1.327	− .711	−.356	− .138	0
.08	A_1	− .557	− .771	− .880	−.941	− .977	−1.000
	A_2	−2.887	−1.493	− .784	−.387	− .149	0
.10	A_1	− .387	− .691	− .840	−.922	− .970	−1.000
	A_2	−3.226	−1.626	− .840	−.410	− .156	0
.15	A_1	(3)	− .426	− .719	−.867	− .950	−1.000
	A_2	(3)	−2.067	−1.014	−.478	− .179	0
.20	A_1	(3)	0	− .546	−.795	− .926	−1.000
	A_2	(3)	−2.778	−1.261	−.568	− .206	0
.25	A_1	(3)	(3)	− .286	−.698	− .895	−1.000
	A_2	(3)	(3)	−1.633	−.690	− .240	0
.30	A_1	(3)	(3)	(3)	−.560	− .855	−1.000
	A_2	(3)	(3)	(3)	−.862	− .285	0

(1)   AQL = Acceptable Quality Level
(2) p_0 = Fraction defective at which the consumer is unwilling to pay anything.
(3)   Values calculated do not satisfy the restrictions given in Table III.

V. VARIOUS CHARACTERISTICS OF THE PROPOSED SAMPLING SCHEME

In this chapter we will examine the general PASS system for sensitivity to changes in its parameters and also investigate the proposed scheme in this regard. Then we will look at the proposed scheme to see if it lends itself to a tabular format similar to that of Military Standard 105D.

A. SENSITIVITY OF THE GENERAL PASS MODEL

In examining the sensitivity of the PASS model, the question which needs to be answered is "How does the selection of parameters, such as A_0, A_1, A_2, and p, affect the required sample size, n. The critical relationship to determine the sensitivity of sample size to these parameters is Equation (13),

$$A_0 + \frac{A_1 x}{n} - \frac{A_2 x}{n(n-1)} + \frac{A_2 x^2}{n(n-1)} - \frac{L}{C}(1-p_1) = 0.$$

If A_0, A_1, and A_2 comply with the restrictions given in Chapter IV, then there is only one root of Equation (13) which is of interest. The smaller root, x_1, is negative and of no relevance in Equation (14). So we have

$$x_2 = \left[\frac{A_2}{n(n-1)} - \frac{A_1}{n} - \sqrt{\left(\frac{A_1}{n} - \frac{A_2}{n(n-1)}\right)^2 - 4\left(A_0 - \frac{L}{C}(1-p_1)\right)\frac{A_2}{n(n-1)}}\right] \Big/ \frac{2A_2}{n(n-1)} . \quad (21)$$

As explained in Chapter III, the procedure for finding the minimum sample size is as follows. Fix n and calculate

31

the value of x_2. Then $\Pr(X \geq x_2)$ is evaluated, using the
cumulative binomial distribution, and compared to α. If
$\Pr(X \geq x_2) > \alpha$, then the sample size is increased which
results in a larger x_2. This is continued until an n is
found such that $\Pr(X \geq x_2) \leq \alpha$. For a given sample size, n, it
is important to see how changes in A_1, A_2, and Z affect x_2,
where Z is defined as $Z = \frac{L}{C}(1-p_1)$. Taking the partial
differentials of Equation (21) results in the following
equations:

$$\frac{\partial x_2}{\partial A_1} = \frac{1-n}{2A_2}\left(1 + \left[\left(\frac{A_1}{n} - \frac{A_2}{n(n-1)}\right)^2 - 4(1-Z)\frac{A_2}{n(n-1)}\right]^{-\frac{1}{2}}\left(\frac{A_1}{n} - \frac{A_2}{n(n-1)}\right)\right),$$

$$\frac{\partial x_2}{\partial A_2} = \frac{A_1(n-1)}{2A_2^2} - \left[\frac{A_2}{n(n-1)}\left[\left(\frac{A_1}{n} - \frac{A_2}{n(n-1)}\right)^2 - 4(1-Z)\frac{A_2}{n(n-1)}\right]^{-\frac{1}{2}}\right.$$

$$\left(\frac{-2}{n(n-1)}\left(\frac{A_1}{n} - \frac{A_2}{n(n-1)}\right)\left(\frac{-4(1-Z)}{n(n-1)}\right)\right) - \left[\left(\frac{A_1}{n} - \frac{A_2}{n(n-1)}\right)^2 - 4(1-Z)\frac{A_2}{n(n-1)}\right]^{\frac{1}{2}}$$

$$\left(\frac{2}{n(n-1)}\right)\bigg/\left(\frac{2A_2}{n(n-1)}\right)^2,$$

and $\frac{\partial x_2}{\partial Z} = \frac{n(1-n)}{A_2}\left[\left(\frac{A_1}{n} - \frac{A_2}{n(n-1)}\right)^2 - 4(1-Z)\frac{A_2}{n(n-1)}\right]^{-\frac{1}{2}}\frac{A_2}{n(n-1)}$.

Although these expressions are very unwieldy, they indicate
the following: x_2 increases as A_1 or A_2 increases. As Z
decreases, x_2 increases, which implies that x_2 increases as
the ratio $\frac{L}{C}$ decreases or as p_1 increases. It should be noted
that in Table IV as the values of A_1 decrease across a row,
the corresponding values of A_2 increase. This behavior
makes the finding that the value of x_2 is directly related

32

to A_1 and A_2 particularly important, since it may be found that for a given p_0, the minimum sample size may depend only on the $\frac{L}{C}$ ratio and not on AQL.

B.   EXAMINING THE PROPOSED MODEL

In order to examine the sensitivity of the proposed scheme, a computer program was written to determine the values of x_2 for each set of the indifference function co-efficients given in Table IV as $\frac{L}{C}$ varied from .9 to 1.0 and as n varied from 10 to 150.   The output of that program is contained in Appendix A.   After setting producer's risk at .05, it was possible to consult a table of cumulative binomial probabilities to determine the minimum value of x_2 for a given n which would result in a probability of occurrence less than or equal to .05.   Table V contains these values of x_2.   Having this table, the minimum value of n, given AQL, p_0, and $\frac{L}{C}$, was found.   This was done by searching each column of the computer output until an x_2, rounded up, was found which was equal to the appropriate entry in Table V.   These minimum values of n are noted in Table VI.   By having these values in a table, it is possible to evaluate if any further consolidation is possible.

As can be seen for small values of AQL and small values of $\frac{L}{C}$, the values of n behave very well in that they change very little for different values of p_0.   However, as either AQL or $\frac{L}{C}$ approaches the upper limits under consideration, the values of n vary widely over the range of p_0.

33

TABLE V

Minimum Number of Defects in a Sample of Size n,
Given an Acceptable Quality Level, to Meet an α of 0.05

AQL	.03	.05	.08	.10	.15	.20	.25	.30
n								
10	2	3	3	4	4	5	6	6
20	3	4	5	5	7	8	9	10
30	4	5	6	7	9	11	12	14
40	4	5	7	8	11	13	16	18
50	5	6	8	10	13	16	19	21
60	5	7	9	11	15	18	22	25
70	6	8	11	12	17	21	25	28
80	6	8	12	14	18	23	27	32
90	7	9	13	15	20	25	30	35
100	7	10	14	16	22	28	33	39
110	7	10	15	17	24	30	36	42
120	8	11	16	19	26	32	39	45
130	8	12	17	20	27	35	42	49
140	9	12	18	21	29	37	45	52
150	9	13	19	22	31	39	47	55

TABLE VI

Minimum Sample Size for a Given AQL, p_0, and $\frac{L}{C}$ Ratio at $\alpha = .05$

AQL	p_0	$\frac{L}{C}$	.90	.91	.92	.93	.94	.95	.96	.97
.03	.5		10	10	10	10	40	40	80	110
	.6		10	10	10	40	40	40	80	110
	.7		10	10	10	40	40	40	80	110
	.8		10	10	10	40	40	40	80	110
	.9		10	10	10	40	40	40	80	110
.05	.5		30	40	40	40	40	40	80	110
	.6		30	40	40	40	40	80	80	140
	.7		30	40	40	40	40	80	80	140
	.8		30	40	40	40	40	80	80	140
	.9		30	40	40	40	40	80	80	>150
.08	.5		30	30	40	40	50	60	110	150
	.6		30	40	40	50	50	100	130	>150
	.7		30	40	40	50	60	110	150	>150
	.8		30	40	40	50	60	120	150	>150
	.9		30	40	40	50	60	120	150	>150
.10	.5		20	40	40	40	60	70	70	110
	.6		40	40	40	60	70	100	110	>150
	.7		40	40	40	60	70	100	150	>150
	.8		40	40	60	70	90	110	>150	>150
	.9		40	40	60	70	100	110	>150	>150
.15	.6		40	50	50	60	80	80	80	130
	.7		50	60	70	80	80	130	130	>150
	.8		50	70	80	80	130	130	>150	>150
	.9		60	80	80	90	130	>150	>150	>150

35

TABLE VI (Continued)

AQL	p_0	$\frac{L}{C}$	.90	.91	.92	.93	.94	.95	.96	.97
.20	.6		40	40	40	40	40	40	60	60
	.7		40	60	60	60	80	90	110	120
	.8		60	60	80	90	120	150	>150	>150
	.9		60	80	90	120	>150	>150	>150	>150
.25	.7		30	30	50	60	70	70	80	80
	.8		70	80	80	80	100	140	150	>150
	.9		80	80	110	150	>150	>150	>150	>150
.30	.8		50	50	70	70	90	90	110	120
	.9		90	110	120	150	>150	>150	>150	>150

36

TABLE VII

Minimum Sample Size Given p_0
And the $\frac{L}{C}$ Ratio for AQL's From 0.03 - 0.30

$\frac{L}{C}$	p_0	.5	.6	.7	.8	.9
.90		20	30	30	50	50
.91		30	30	30	50	50
.92		30	30	40	60	80
.93		30	50	50	70	110
.94		50	50	70	70	110
.95		60	80	80	90	150
.96		80	90	100	140	(1)
.97		110	140	150	(1)	(1)

(1) Minimum sample size exceeds 150.

If AQL's of .10 or less are assumed to be the area of
interest, it is apparent that a simple table using AQL and
$\frac{L}{C}$ as references could be used to determine a "good" value
of n. However, when the wider range of AQL's (.03 - .30)
was considered, it appeared more useful to create a table
based on cross referencing p_0 and $\frac{L}{C}$. Table VII was developed
using the criteria that the sample size should be minimized
subject to producer's risk being kept between 0.01 and 0.10.
This range can be compared to producer's risk in Military
Standard 105D which varies from .01 to .11. This objective
was achieved with the exception of the starred entries in
Table VII where sample sizes larger than 150 would have been
required.

Using Table VII in conjunction with Table IV, it is
possible to find a sampling plan for any of the identified
AQL and p_0 values. Having found the desired plan, the last
item of interest would be to see what kind of operating
characteristic curves the plan would have.

C. OPERATING CHARACTERISTIC CURVES

It is of interest to show how payments will vary over
the range of p rather than at just two points, the AQL and
p_0. To satisfy this need, operating characteristic curves
may be developed. Having established a plan, we know sample
size and the indifference function, h(p). It is now

possible to calculate the expected price per satisfactory item, $C(p)$,

$$C(p) = \frac{E[P_t]}{N(1-p)} = \frac{C(1 + A_1 p + A_2 p^2)}{(1-p)} \ .$$

In addition to a plot of $C(p)$, a complete set of operating characteristic curves would include a plot of two other functions, the "lower," $L(p)$, and "upper," $U(p)$, price per satisfactory item. They correspond, respectively, to a chosen α and β. Here, $L(p)$ and $U(p)$ are defined as

$$L(p) = \frac{C \ Q(k_1)}{1-p} \ ,$$

and $$U(p) = \frac{C \ Q(k_2)}{1-p} \ ,$$

where k_1 and k_2 are values of x which, for a given p, satisfy the limits set for producer's or consumer's risk. This concept is best clarified by an example.

D. AN EXAMPLE

Suppose that a government agency is contracting out for bus service and that it has been decided that an acceptable quality level would be that buses could be off schedule ten percent of the time, i.e., AQL = .10. It has also been decided that if buses aren't on time eighty percent of the time, then the contractor should be paid nothing, i.e., $p_0 = 0.8$. In order to attract bids, it is decided that the lower limit should be set at ninety-five percent of the

39

average price paid for a good item, i.e., $\frac{L}{C} = 0.95$. Using this information, we find from Table IV that $A_1 = -.922$ and $A_2 = 0.410$ and, from Table VII, $n = 90$. From this we have

$$C(p) = C(1 - .922\,p - .41\,p^2) / (1-p) ,$$

$$L(p) = C\left(1 - \frac{.922}{90}\,k_1 + \frac{.41}{90(89)}\,k_1 - \frac{.41}{90(89)}\,k_1{}^2\right) / (1-p) ,$$

$$\text{and } U(p) = C\left(1 - \frac{.922}{90}\,k_2 + \frac{.41}{90(89)}\,k_2 - \frac{.41}{90(89)}\,k_2{}^2\right) / (1-p).$$

These equations are solved for various values of p and the resultant functional values are given in Table VIII. To find any k value, a cumulative binomial probability table can be used and an x can be found which satisfies the risk requirements. If $p = 0.03$, $n = 90$, and $\alpha = 0.05$, then $k_1 = 7$; if $\alpha = 0.005$, then k_1 would $= 9$. As can be seen fro⌐ Table VIII, the possibility of wide variation from C(p) increases dramatically as p increases. Another feature, which the table points out, is that negative payments are possible. This is not surprising, since the customer in identifying p_0 has established the point beyond which the supplier's poor performance actually results in damages to the customer beyond the value of whatever good items have been received in the lot.

TABLE VIII

Operating Characteristic Curve Values

p	k_1 [1]	k_2 [2]	L(p)	C(p)	U(p)
.03	7	1	.955	1.002	1.020
.05	9	2	.952	1.003	1.031
.08	13	4	.934	1.004	1.042
.10	15	5	.928	1.004	1.057
.15	20	9	.913	1.003	1.064
.20	25	13	.891	.999	1.074
.25	30	17	.864	.992	1.083
.30	35	21	.829	.981	1.091
.40	45	30	.729	.943	1.080
.50	54	39	.601	.873	1.049
.60	63	41	.387	.748	.982
.70	71	57	.061	.512	.842
.80	79	67	− .624	.000	.436
.90	86	77	-2.552	-1.619	− .883

(1) k_1 figured at α = .05.

(2) k_2 figured at β = .10.

VI. CONCLUSIONS AND RECOMMENDATIONS

In summary, the basic quantities needed to complete a
PASS plan, with quadratic indifference, are n, the sample
size, and h(p), the indifference function. By using the
idea suggested by Military Standard 105D of maximizing the
price paid per nondefective item at the AQL, by noting the
restrictions on the coefficients of the indifference
function, and by defining h(p) to be 0 at p_0, it was possi-
ble to develop the proposed system which determined a set
of indifference functions based on the values of AQL and
p_0. Then a simplified method of finding sample size was
presented which kept producer's risk between one and ten
percent. Finally, the method for determining the proposed
system's Operating Characteristics Curves was illustrated.

In order to implement the proposed system, only AQL,
p_0, and the $\frac{L}{C}$ ratio need to be known. With this information
n and P_t, the payment function, can be found. After in-
specting n items from a lot of size N, the number of defective
items, x, will be known and the value P_t can be paid to the
supplier.

The primary purpose of applying PASS, and also the
proposed system, is to eliminate the necessity of rejecting
lots. This is of particular advantage when the customer
would rather not reject the lot, in the case of a badly needed

42

part, or cannot reject the lot, in the case of having services performed. The added advantage of the proposed system is that it eliminates the problem of identifying the indifference function and it shortens the time required to find n.

A. RECOMMENDATIONS FOR FURTHER STUDY

The following are recommended areas for further study:

1. It may be possible to develop a set of switching rules for the proposed system, similar to those in Military Standard 105D.

2. An area consciously omitted from this study was the problem of how to determine NC, the total price paid if $p = 0$.

3. In all probability the actual operating region for a supplier should be in the vicinity of the AQL. It may be possible to use a linear approximation to the indifference function in that region.

4. It may be enlightening to determine what effect increasing sample size (for a given indifference function) would have on the spread between $U(p)$ and $L(p)$.

5. Betty Flehinger and James Miller [3] have done a paper on price paid being dependent on sampling; however, the detailed analysis is considered for repairable systems. The scheme proposed in this paper is more oriented toward non-repairable systems.

43

An analysis along the lines of ref. 3 for non-repairable systems, keeping PASS in mind could be interesting.

It is hoped that this work will not only be useful to those faced with the problem of being required to accept lots and needing a means to adjust price, but will also generate interest in further studies in this area.

APPENDIX A

Solutions to Equation (21)

AQL=0.03   PO=0.50

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10	1.3	1.3	1.2	1.1	1.0	0.9	0.8	0.7	0.6	0.5	0.4
20	2.4	2.4	2.1	2.0	1.8	1.7	1.5	1.3	1.1	0.9	0.7
30	3.6	3.4	3.1	2.9	2.5	2.4	2.2	1.9	1.6	1.3	1.0
40	4.8	4.5	4.1	3.8	3.3	3.2	2.9	2.5	2.1	1.7	1.4
50	6.0	5.5	5.1	4.7	4.2	3.9	3.6	3.1	2.6	2.2	1.7
60	7.0	6.6	6.1	5.5	5.0	4.7	4.2	3.7	3.1	2.6	2.0
70	8.1	7.6	7.1	6.4	5.8	5.4	4.9	4.3	3.6	3.0	2.3
80	9.2	8.7	8.0	7.3	6.7	6.2	5.6	4.8	4.1	3.4	2.6
90	10.5	9.8	9.0	8.3	7.5	6.9	6.2	5.4	4.6	3.8	2.9
100	11.6	10.8	10.0	9.3	8.3	7.7	6.9	6.0	5.1	4.2	3.3
110	12.6	11.9	11.0	10.2	9.3	8.4	7.6	6.6	5.6	4.6	3.6
120	13.7	13.0	12.0	11.2	10.2	9.2	8.2	7.2	6.1	5.1	3.9
130	14.9	13.9	13.0	12.0	11.0	10.0	8.9	7.8	6.7	5.5	4.2
140	16.0	15.0	14.0	12.9	11.8	10.7	9.6	8.4	7.2	5.9	4.5
150	17.1	16.1	15.0	13.8	12.7	11.5	10.3	9.0	7.7	6.3	4.9

AQL=0.03   PO=0.60

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10	1.3	1.2	1.1	1.0	1.0	0.9	0.8	0.7	0.6	0.5	0.4
20	2.5	2.3	2.1	2.0	1.8	1.6	1.4	1.3	1.1	0.9	0.7
30	3.7	3.5	3.2	2.9	2.7	2.4	2.1	1.8	1.6	1.3	1.0
40	4.8	4.6	4.2	3.8	3.5	3.1	2.8	2.4	2.1	1.7	1.3
50	6.2	5.7	5.2	4.7	4.2	3.9	3.5	3.0	2.6	2.2	1.7
60	7.4	6.8	6.3	5.7	5.1	4.7	4.2	3.6	3.1	2.5	2.0
70	8.6	7.9	7.3	6.7	6.0	5.5	4.9	4.2	3.6	3.1	2.2
80	9.6	8.9	8.3	7.6	6.8	6.2	5.6	4.8	4.1	3.4	2.5
90	10.8	10.0	9.3	8.5	7.6	7.0	6.2	5.4	4.6	3.7	2.8
100	11.9	11.1	10.3	9.5	8.6	7.8	6.9	6.0	5.1	4.2	3.1
110	13.1	12.2	11.3	10.4	9.3	8.5	7.6	6.6	5.6	4.5	3.4
120	14.3	13.3	12.4	11.4	10.2	9.3	8.2	7.2	6.1	5.1	3.8
130	15.5	14.4	13.4	12.3	11.2	10.0	8.9	7.7	6.6	5.5	4.1
140	16.7	15.6	14.4	13.2	12.0	10.8	9.6	8.3	7.1	5.7	4.4
150	17.9	16.7	15.4	14.2	12.9	11.6	10.3	8.9	7.6	6.1	4.7

AQL=0.03 PO=0.70

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		1.3	1.2	1.1	1.0	0.9	0.8	0.7	0.6	0.5	0.4	0.3
200		2.5	2.3	2.2	2.0	1.8	1.6	1.4	1.2	1.0	0.8	0.6
300		3.7	3.5	3.2	2.9	2.7	2.4	2.1	1.8	1.5	1.2	0.9
400		4.9	4.6	4.2	3.9	3.5	3.1	2.8	2.4	2.0	1.6	1.2
500		6.2	5.7	5.3	4.8	4.4	3.9	3.5	3.0	2.5	2.0	1.5
600		7.4	6.9	6.3	5.8	5.2	4.7	4.1	3.6	3.0	2.4	1.8
700		8.6	8.0	7.4	6.7	6.1	5.5	4.8	4.2	3.5	2.8	2.1
800		9.8	9.1	8.4	7.7	7.0	6.3	5.5	4.8	4.0	3.2	2.5
900		11.0	10.3	9.5	8.6	7.8	7.0	6.2	5.4	4.5	3.6	2.8
1000		12.3	11.4	10.5	9.6	8.7	7.8	6.9	5.9	5.0	4.0	3.1
1100		13.5	12.5	11.6	10.6	9.6	8.6	7.6	6.5	5.5	4.5	3.4
1200		14.7	13.7	12.6	11.5	10.3	9.4	8.2	7.1	6.0	4.9	3.7
1300		15.9	14.8	13.6	12.5	11.3	10.1	8.9	7.7	6.5	5.3	4.0
1400		17.1	15.9	14.7	13.4	12.2	10.9	9.6	8.3	7.0	5.7	4.3
1500		18.4	17.0	15.7	14.4	13.0	11.7	10.3	8.9	7.5	6.1	4.6

AQL=0.03 PO=0.80

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		1.3	1.2	1.1	1.0	0.9	0.8	0.7	0.6	0.5	0.4	0.3
200		2.5	2.3	2.2	2.0	1.8	1.6	1.4	1.2	1.0	0.8	0.6
300		3.8	3.5	3.2	2.9	2.6	2.4	2.1	1.8	1.5	1.2	0.9
400		5.0	4.6	4.3	3.9	3.4	3.1	2.8	2.4	2.0	1.6	1.2
500		6.2	5.8	5.3	4.8	4.3	3.9	3.5	3.0	2.5	2.0	1.5
600		7.5	6.9	6.4	5.8	5.1	4.7	4.1	3.6	3.0	2.4	1.8
700		8.7	8.1	7.4	6.8	6.0	5.5	4.8	4.2	3.5	2.8	2.1
800		10.0	9.2	8.5	7.7	6.9	6.3	5.5	4.7	4.0	3.2	2.4
900		11.2	10.4	9.6	8.7	7.8	7.0	6.2	5.3	4.5	3.6	2.7
1000		12.5	11.5	10.6	9.7	8.6	7.8	6.9	5.9	5.0	4.0	3.0
1100		13.8	12.7	11.7	10.7	9.5	8.4	7.6	6.5	5.5	4.4	3.3
1200		14.9	13.8	12.7	11.6	10.4	9.2	8.3	7.1	6.0	4.8	3.6
1300		16.2	15.0	13.8	12.6	11.3	10.2	8.9	7.7	6.5	5.2	3.9
1400		17.4	16.2	14.9	13.6	12.3	10.9	9.6	8.3	7.0	5.6	4.3
1500		18.7	17.3	15.9	14.5	13.1	11.7	10.3	8.9	7.5	6.0	4.6

46

L/C

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100	1.3	1.2	1.1	1.0	0.9	0.8	0.7	0.6	0.5	0.4	0.3
200	2.5	2.3	2.2	2.0	1.8	1.6	1.4	1.2	1.0	0.8	0.6
300	3.8	3.5	3.2	2.9	2.6	2.4	2.1	1.8	1.5	1.2	0.9
400	5.1	4.7	4.3	3.9	3.5	3.1	2.8	2.4	2.0	1.6	1.2
500	6.3	5.8	5.4	4.9	4.4	3.9	3.4	3.0	2.5	2.0	1.5
600	7.6	7.0	6.4	5.8	5.3	4.7	4.1	3.6	3.0	2.4	1.8
700	8.8	8.2	7.5	6.8	6.2	5.5	4.8	4.1	3.5	2.8	2.1
800	10.1	9.3	8.6	7.8	7.0	6.3	5.5	4.7	4.0	3.2	2.4
900	11.3	10.5	9.6	8.8	7.9	7.1	6.2	5.3	4.5	3.6	2.7
1000	12.6	11.7	10.7	9.7	8.8	7.8	6.9	5.9	5.0	4.0	3.0
1100	13.9	12.8	11.8	10.7	9.7	8.6	7.6	6.5	5.5	4.4	3.3
1200	15.1	14.0	12.8	11.7	10.6	9.4	8.3	7.1	6.0	4.8	3.6
1300	16.4	15.2	13.9	12.7	11.4	10.2	8.9	7.7	6.4	5.2	3.9
1400	17.6	16.3	15.0	13.7	12.3	11.0	9.6	8.3	6.9	5.6	4.2
1500	18.9	17.5	16.1	14.6	13.2	11.8	10.3	8.9	7.4	6.0	4.5

PO=0.50

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		1.6	1.5	1.4	1.4	1.3	1.2	1.1	1.0	0.9	0.8	0.7
200		2.9	2.7	2.6	2.5	2.3	2.1	2.0	1.8	1.6	1.5	1.3
300		4.2	4.0	3.8	3.6	3.4	3.1	2.9	2.6	2.4	2.1	1.8
400		5.5	5.3	5.0	4.7	4.4	4.1	3.8	3.4	3.1	2.7	2.4
500		6.9	6.5	6.2	5.8	5.4	5.1	4.7	4.3	3.8	3.4	3.5
600		8.2	7.8	7.4	6.9	6.5	6.0	5.6	5.1	4.6	4.0	4.6
700		9.5	9.1	8.6	8.1	7.5	7.0	6.5	5.9	5.3	4.7	5.1
800		10.9	10.3	9.8	9.2	8.6	8.0	7.4	6.7	6.0	5.3	5.7
900		12.2	11.6	10.1	10.4	9.6	9.0	8.2	7.5	6.8	6.0	6.3
1000		13.5	12.8	12.1	11.5	10.7	9.9	9.1	8.3	7.5	6.6	6.8
1100		14.9	14.1	13.3	12.5	11.7	10.9	10.0	9.1	8.2	7.3	7.4
1200		16.2	15.4	14.5	13.7	12.8	11.9	10.9	10.0	9.0	7.9	7.9
1300		17.5	16.6	15.7	14.8	13.8	12.9	11.8	10.8	9.7	8.6	8.5
1400		18.8	17.9	16.9	15.9	14.9	13.8	12.7	11.6	10.4	9.2	
1500		20.2	19.2	18.1	17.0	15.9	14.8	13.6	12.4	11.2	9.9	

PO=0.60

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		1.5	1.4	1.4	1.3	1.2	1.1	1.0	0.9	0.8	0.7	0.6
200		2.9	2.7	2.6	2.4	2.2	2.1	1.9	1.7	1.5	1.3	1.2
300		4.2	4.0	3.8	3.6	3.3	3.1	2.8	2.5	2.2	2.0	1.7
400		5.6	5.3	5.0	4.7	4.4	4.0	3.7	3.3	2.9	2.6	2.3
500		7.0	6.6	6.2	5.8	5.4	5.0	4.5	4.1	3.7	3.2	3.0
600		8.4	7.9	7.4	7.0	6.5	6.0	5.4	4.9	4.4	3.8	3.8
700		9.8	9.2	8.7	8.1	7.5	6.9	6.3	5.7	5.1	4.7	4.8
800		11.1	10.5	9.9	9.2	8.6	7.9	7.2	6.5	5.8	5.3	5.4
900		12.5	11.8	11.1	10.4	9.7	8.9	8.1	7.3	6.5	6.0	6.0
1000		13.9	13.1	12.3	11.7	10.7	9.9	9.0	8.1	7.2	6.6	6.4
1100		15.3	14.4	13.5	12.7	11.7	10.8	9.8	8.9	7.9	7.3	7.0
1200		16.6	15.7	14.8	13.9	12.8	11.8	10.7	9.7	8.7	8.2	7.5
1300		18.0	17.0	16.0	14.9	13.9	12.8	11.6	10.5	9.4	8.8	8.0
1400		19.4	18.3	17.2	16.1	14.9	13.8	12.6	11.3	10.1	9.4	
1500		20.8	19.6	18.4	17.2	16.0	14.7	13.4	12.1	10.8		

AQL=0.05   PO=0.70

N	L/C 0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100	1.5	1.4	1.3	1.2	1.1	1.0	0.9	0.9	0.8	0.7	0.6
200	2.9	2.7	2.5	2.4	2.2	2.0	1.8	1.6	1.5	1.3	1.1
300	4.3	4.0	3.8	3.5	3.3	3.0	2.7	2.4	2.2	1.9	1.6
400	5.7	5.4	5.0	4.7	4.3	4.0	3.6	3.2	2.9	2.5	2.1
500	7.1	6.7	6.3	5.8	5.4	4.9	4.5	4.0	3.6	3.1	2.6
600	8.5	8.0	7.5	7.0	6.5	5.9	5.4	4.8	4.3	3.7	3.1
700	9.9	9.3	8.7	8.1	7.6	6.9	6.3	5.6	5.0	4.3	3.7
800	11.3	10.6	10.0	9.3	8.6	7.8	7.1	6.4	5.7	4.9	4.2
900	12.7	12.0	11.2	10.4	9.6	8.8	8.0	7.2	6.4	5.5	4.7
1000	14.1	13.3	12.4	11.6	10.7	9.8	8.9	8.0	7.1	6.1	5.2
1100	15.6	14.6	13.7	12.7	11.8	10.8	9.7	8.8	7.8	6.8	5.7
1200	17.0	15.9	14.9	13.9	12.9	11.7	10.7	9.6	8.5	7.4	6.2
1300	18.4	17.3	16.1	15.0	13.9	12.7	11.6	10.4	9.2	8.0	6.8
1400	19.8	18.6	17.4	16.2	14.9	13.7	12.4	11.2	9.9	8.6	7.3
1500	21.2	19.9	18.6	17.3	16.0	14.7	13.3	12.0	10.6	9.2	7.8

AQL=0.05   PO=0.80

N	L/C 0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100	1.5	1.4	1.3	1.2	1.1	1.0	0.9	0.8	0.7	0.6	0.5
200	2.9	2.7	2.5	2.4	2.2	2.0	1.8	1.6	1.4	1.2	1.0
300	4.3	4.1	3.8	3.5	3.3	3.0	2.7	2.4	2.1	1.8	1.5
400	5.8	5.4	5.0	4.7	4.3	4.0	3.6	3.2	2.8	2.4	2.0
500	7.2	6.7	6.3	5.8	5.4	4.9	4.4	4.0	3.5	3.0	2.6
600	8.6	8.1	7.5	7.0	6.5	5.9	5.3	4.8	4.2	3.6	3.1
700	10.0	9.4	8.8	8.1	7.6	6.9	6.2	5.6	4.9	4.2	3.6
800	11.5	10.7	10.0	9.3	8.6	7.8	7.1	6.3	5.6	4.8	4.1
900	12.9	12.1	11.2	10.4	9.6	8.8	8.0	7.1	6.3	5.4	4.6
1000	14.3	13.4	12.5	11.6	10.8	9.8	8.7	7.9	7.0	6.1	5.1
1100	15.7	14.8	13.8	12.8	11.8	10.7	9.6	8.7	7.7	6.7	5.6
1200	17.2	16.1	15.0	13.9	12.9	11.7	10.5	9.5	8.4	7.3	6.1
1300	18.6	17.4	16.3	15.1	13.9	12.7	11.4	10.3	9.1	7.9	6.6
1400	20.0	18.8	17.5	16.2	15.0	13.7	12.4	11.1	9.8	8.5	7.1
1500	21.5	20.1	18.8	17.4	16.0	14.7	13.3	11.9	10.5	9.1	7.6

AQL=0.05   PO=0.90

N	L/C										
	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100	1.5	1.4	1.3	1.2	1.1	1.0	0.9	0.8	0.7	0.6	0.5
200	2.9	2.7	2.5	2.3	2.2	2.0	1.8	1.6	1.4	1.2	1.0
300	4.3	4.1	3.8	3.5	3.3	2.9	2.7	2.4	2.1	1.8	1.5
400	5.8	5.4	5.0	4.7	4.4	3.9	3.5	3.2	2.8	2.4	2.0
500	7.2	6.8	6.3	5.8	5.5	4.9	4.4	3.9	3.5	3.0	2.5
600	8.7	8.1	7.5	7.0	6.6	5.8	5.3	4.7	4.2	3.6	3.0
700	10.1	9.4	8.8	8.1	7.6	6.8	6.2	5.5	4.9	4.2	3.5
800	11.5	10.8	10.1	9.3	8.6	7.8	7.1	6.3	5.5	4.8	4.0
900	13.0	12.1	11.3	10.5	9.7	8.7	7.9	7.1	6.2	5.4	4.5
1000	14.4	13.5	12.6	11.6	10.8	9.7	8.8	7.9	6.9	6.0	5.0
1100	15.9	14.8	13.8	12.8	11.8	10.7	9.7	8.7	7.6	6.6	5.5
1200	17.3	16.2	15.1	14.0	12.9	11.7	10.6	9.5	8.3	7.2	6.0
1300	18.7	17.5	16.3	15.1	13.9	12.7	11.5	10.2	9.0	7.8	6.5
1400	20.2	18.9	17.6	16.3	15.0	13.7	12.3	11.0	9.7	8.4	7.0
1500	21.6	20.2	18.8	17.4	16.0	14.6	13.2	11.8	10.4	9.0	7.6

AQL=0.08   PO=0.50

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		2.0	1.9	1.9	1.8	1.7	1.6	1.6	1.5	1.4	1.3	1.3
200		3.6	3.5	3.4	3.2	3.1	3.0	2.8	2.7	2.5	2.3	2.2
300		5.3	5.1	4.9	4.7	4.5	4.3	4.1	3.8	3.6	3.4	3.1
400		6.8	6.7	6.4	6.6	5.9	5.6	5.3	5.0	4.7	4.4	4.0
500		8.6	8.0	7.9	7.6	7.3	6.9	6.6	6.2	5.8	5.4	5.0
600		10.2	9.9	9.5	9.1	8.7	8.3	7.9	7.4	7.0	6.5	6.0
700		11.5	11.1	11.0	10.6	10.1	9.6	9.1	8.6	8.1	7.5	6.9
800		13.5	13.1	12.6	12.0	11.5	10.3	10.4	9.8	9.2	8.6	7.9
900		15.2	14.3	14.1	13.5	12.9	12.6	11.6	11.0	10.4	9.6	8.8
1000		16.5	16.3	15.6	15.0	14.3	13.6	12.9	12.2	11.5	10.7	10.8
1100		18.2	17.8	17.2	16.4	15.7	15.0	14.2	13.4	12.7	11.7	11.7
1200		20.2	19.4	18.7	17.9	17.1	16.6	15.4	14.6	13.7	12.7	12.7
1300		21.8	21.0	20.2	19.4	18.5	17.6	16.7	15.8	14.8	13.8	13.7
1400		23.5	22.6	21.8	20.9	19.9	19.0	18.0	17.0	15.9	14.8	14.6
1500		25.2	24.2	23.3	22.3	21.3	20.3	19.2	18.1	17.0	15.8	14.6

AQL=0.08   PO=0.60

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		1.9	1.8	1.7	1.6	1.6	1.5	1.4	1.3	1.2	1.1	1.0
200		3.5	3.4	3.2	3.1	2.9	2.8	2.6	2.4	2.3	2.1	1.9
300		5.2	5.0	4.8	4.5	4.3	4.1	3.8	3.6	3.4	3.1	2.8
400		6.9	6.6	6.3	6.0	5.7	5.4	5.0	4.7	4.4	4.0	3.7
500		8.6	8.2	7.8	7.5	7.1	6.7	6.3	5.9	5.5	5.0	4.5
600		10.3	9.8	9.4	8.9	8.5	8.0	7.5	7.0	6.6	6.0	5.4
700		11.6	11.4	10.4	10.4	9.2	9.3	8.9	8.3	8.7	7.9	7.2
800		13.3	13.7	12.4	11.8	11.2	10.9	11.2	10.6	9.7	8.9	8.0
900		15.3	14.3	14.0	13.3	12.6	12.5	12.6	11.7	10.7	9.8	9.9
1000		17.0	16.3	15.5	14.2	14.4	13.8	14.0	12.9	11.8	10.8	10.7
1100		18.7	17.9	17.6	16.2	16.7	15.8	14.8	13.9	12.8	12.0	11.6
1200		20.4	19.5	18.6	17.7	16.7	17.1	16.1	15.0	13.8	12.8	12.5
1300		22.0	21.1	20.1	19.1	18.1	18.4	17.3	16.1	15.0	13.8	13.4
1400		23.7	22.7	21.7	20.6	18.5	19.7	18.5	17.3	16.0	14.7	13.4
1500		25.4	24.3	23.2	22.1	20.9	19.7	18.5	17.3	16.0	14.7	13.4

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
L/C											
100	1.8	1.7	1.6	1.6	1.5	1.4	1.3	1.2	1.1	1.0	0.9
200	3.5	3.3	3.2	3.0	2.8	2.7	2.5	2.3	2.1	1.9	1.8
300	5.2	4.9	4.7	4.5	4.2	4.1	3.7	3.5	3.2	2.9	2.6
400	6.9	6.6	6.2	5.9	5.6	5.2	4.9	4.6	4.2	3.7	3.4
500	8.6	8.2	7.8	7.4	6.9	6.5	6.1	5.8	5.2	4.7	4.3
600	10.3	9.8	9.3	8.8	8.3	7.8	7.3	6.9	6.2	5.6	5.1
700	12.0	11.4	10.8	10.3	9.7	9.1	8.5	8.0	7.2	6.6	6.0
800	13.7	13.0	12.4	11.7	11.0	10.4	9.7	9.1	8.3	7.5	6.8
900	15.4	14.6	13.9	13.2	12.4	11.6	10.9	10.2	9.3	8.4	7.7
1000	17.1	16.3	15.4	14.6	13.8	12.9	12.1	11.3	10.3	9.4	8.5
1100	18.8	17.9	17.0	16.1	15.1	14.2	13.3	12.4	11.4	10.4	9.4
1200	20.5	19.5	18.5	17.5	16.5	15.5	14.5	13.4	12.4	11.3	10.2
1300	22.2	21.1	20.1	19.0	17.9	16.8	15.7	14.5	13.4	12.2	11.1
1400	23.9	22.7	21.6	20.4	19.3	18.1	16.9	15.6	14.4	13.2	11.9
1500	25.6	24.4	23.1	21.9	20.6	19.4	18.1	16.8	15.4	14.1	12.7

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
L/C											
100	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.1	1.0	1.0	0.9
200	3.5	3.3	3.1	2.9	2.8	2.6	2.4	2.2	2.0	1.8	1.7
300	5.2	4.9	4.7	4.4	4.1	3.9	3.6	3.3	3.0	2.7	2.5
400	6.9	6.5	6.2	5.8	5.5	5.1	4.8	4.4	4.0	3.6	3.4
500	8.6	8.2	7.7	7.3	6.9	6.4	6.0	5.5	5.1	4.5	4.2
600	10.3	9.8	9.3	8.7	8.2	7.7	7.1	6.6	6.1	5.4	5.0
700	12.0	11.4	10.8	10.2	9.6	9.0	8.3	7.7	7.1	6.3	5.8
800	13.7	13.0	12.3	11.6	10.9	10.2	9.5	8.8	8.1	7.3	6.7
900	15.4	14.6	13.9	13.1	12.3	11.5	10.7	9.9	9.1	8.2	7.5
1000	17.1	16.3	15.4	14.5	13.7	12.8	11.9	11.0	10.1	9.1	8.3
1100	18.8	17.9	16.9	16.0	15.0	14.0	13.1	12.1	11.1	10.0	9.1
1200	20.5	19.5	18.5	17.4	16.4	15.3	14.2	13.2	12.1	10.9	9.9
1300	22.3	21.1	20.0	18.9	17.7	16.6	15.4	14.3	13.1	11.9	10.7
1400	24.0	22.8	21.5	20.3	19.1	17.9	16.6	15.4	14.1	12.8	11.6
1500	25.7	24.4	23.1	21.8	20.5	19.1	17.8	16.5	15.1	13.7	12.4

AQL=0.08   PO=0.90

N	L/C 0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10	1.7	1.6	1.6	1.5	1.4	1.3	1.2	1.1	1.0	0.9	0.8
20	3.5	3.3	3.1	2.9	2.7	2.5	2.4	2.2	2.0	1.8	1.6
30	5.2	4.9	4.6	4.4	4.1	3.8	3.5	3.3	3.0	2.7	2.4
40	6.9	6.5	6.2	5.8	5.4	5.1	4.7	4.4	4.0	3.6	3.2
50	8.6	8.2	7.7	7.2	6.8	6.3	5.9	5.4	5.0	4.5	4.1
60	10.3	9.8	9.2	8.7	8.2	7.6	7.1	6.5	6.0	5.4	4.9
70	12.0	11.4	10.8	10.1	9.5	8.9	8.2	7.6	7.0	6.3	5.7
80	13.7	13.0	12.3	11.6	10.9	10.1	9.4	8.7	8.0	7.2	6.5
90	15.5	14.7	13.8	13.0	12.2	11.4	10.6	9.8	8.9	8.1	7.3
100	17.2	16.3	15.4	14.5	13.6	12.7	11.8	10.9	9.9	9.0	8.1
110	18.9	17.9	16.9	15.9	14.9	13.9	12.9	11.9	10.9	9.9	8.9
120	20.6	19.5	18.5	17.4	16.3	15.2	14.1	13.0	11.9	10.8	9.7
130	22.3	21.2	20.0	18.8	17.6	16.5	15.3	14.1	12.9	11.7	10.5
140	24.0	22.8	21.5	20.3	19.0	17.7	16.5	15.2	13.9	12.6	11.3
150	25.8	24.4	23.1	21.7	20.4	19.0	17.6	16.3	14.9	13.5	12.1

53

AQL=0.10 PO=0.50

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10		2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.6
20		4.1	4.0	3.9	3.8	3.7	3.5	3.4	3.3	3.1	3.0	2.9
30		6.0	5.7	5.7	5.2	5.0	5.1	5.0	4.2	4.5	4.7	4.1
40		7.8	7.7	7.5	7.0	6.3	6.7	6.5	6.2	5.9	5.7	5.4
50		9.7	9.5	9.2	9.7	8.0	8.3	8.0	7.7	7.3	7.0	6.9
60		11.7	11.4	11.0	10.4	10.3	9.5	9.5	9.2	8.1	8.3	7.9
70		13.5	13.2	12.8	12.4	12.3	11.7	11.6	10.6	10.5	9.6	9.4
80		15.4	15.1	14.6	14.9	13.6	13.3	12.6	12.6	11.9	11.3	10.6
90		17.4	16.9	16.2	15.6	15.0	16.3	14.2	13.5	12.4	12.6	12.9
100		19.3	18.7	18.2	17.3	17.0	17.7	15.7	15.0	14.8	13.0	14.2
110		21.2	20.6	20.7	19.3	18.3	19.6	17.2	16.5	15.2	15.6	15.4
120		23.0	22.4	21.5	21.0	20.6	21.2	18.8	18.0	18.6	16.6	16.7
130		25.0	24.3	23.5	22.8	22.6	22.8	20.3	19.5	20.0	17.6	17.9
140		26.9	26.1	25.3	24.5	23.6	24.4	21.9	20.9	21.4	19.0	19.2
150		28.8	28.0	27.1	26.2	25.3		23.4	22.4		20.3	

AQL=0.10 PO=0.60

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10		2.1	2.1	2.0	1.9	1.8	1.8	1.7	1.6	1.5	1.4	1.3
20		4.0	3.9	3.7	3.6	3.4	3.3	3.1	3.0	2.8	2.6	2.5
30		5.9	5.7	5.5	5.3	5.0	4.8	4.6	4.3	4.1	3.9	3.6
40		7.8	7.5	7.2	6.9	6.6	6.3	6.0	5.7	5.4	5.1	4.7
50		9.7	9.3	9.0	8.6	8.3	7.9	7.5	7.2	6.8	6.3	5.9
60		11.5	11.2	10.8	10.4	10.0	9.6	9.2	8.8	8.4	8.0	7.0
70		13.5	13.0	12.6	12.1	11.7	11.2	10.7	10.3	9.9	9.3	8.1
80		15.4	14.8	14.3	13.7	13.2	12.7	12.1	11.6	11.2	10.4	9.3
90		17.3	16.7	16.0	15.4	14.9	14.3	13.7	13.2	12.5	11.6	10.4
100		19.2	18.5	17.8	17.1	16.5	15.9	15.2	14.6	14.0	12.9	11.4
110		21.2	20.3	19.6	18.8	18.0	17.4	16.6	16.0	15.1	14.4	12.7
120		23.0	22.2	21.3	20.4	19.6	18.7	17.9	17.2	16.5	16.1	13.8
130		24.9	24.0	23.1	22.1	21.2	20.2	19.2	18.2	17.3	17.3	15.0
140		26.8	25.8	24.8	23.8	22.8	21.7	20.7	19.6	18.5	18.5	16.1
150		28.7	27.7	26.6	25.5	24.4	23.3	22.1	21.0	19.8		17.3

54

AQL=0.10 PO=0.70

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10	2.0	1.9	1.9	1.8	1.7	1.6	1.5	1.4	1.4	1.3	1.2
20	3.9	3.8	3.6	3.4	3.3	3.1	2.9	2.8	2.6	2.4	2.2
30	5.8	5.6	5.3	5.1	4.9	4.6	4.4	4.1	3.8	3.6	3.3
40	7.7	7.4	7.1	6.8	6.4	6.1	5.8	5.4	5.1	4.7	4.4
50	9.5	9.2	8.8	8.4	8.0	7.6	7.2	6.8	6.4	5.9	5.5
60	11.4	11.0	10.6	10.1	9.6	9.1	8.6	8.1	7.6	7.1	6.5
70	13.4	12.7	12.3	11.8	11.2	10.6	10.0	9.4	8.9	8.2	7.6
80	15.2	14.7	14.1	13.4	12.8	12.1	11.4	10.8	10.1	9.4	8.7
90	17.1	16.5	15.5	15.1	14.3	13.6	12.9	12.1	11.3	10.7	9.8
100	19.1	18.3	17.5	16.7	15.5	15.1	14.3	13.4	12.6	11.8	10.8
110	21.0	20.2	19.3	18.4	17.1	16.6	15.7	14.8	13.8	12.9	11.9
120	22.9	22.0	21.0	20.1	19.1	18.1	17.1	16.1	15.1	14.0	13.0
130	24.8	23.8	22.8	21.7	20.7	19.6	18.5	17.4	16.3	15.2	14.1
140	26.7	25.6	24.5	23.4	22.3	21.1	19.9	18.8	17.6	16.4	15.1
150	28.6	27.4	26.3	25.1	23.8	22.6	21.4	20.1	18.8	17.5	16.2

AQL=0.10 PO=0.80

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10	2.0	1.9	1.8	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.1
20	3.9	3.7	3.5	3.4	3.2	3.0	2.8	2.7	2.5	2.3	2.1
30	5.8	5.5	5.3	5.0	4.7	4.5	4.2	4.0	3.7	3.4	3.1
40	7.7	7.3	7.0	6.6	6.3	6.0	5.6	5.3	4.9	4.5	4.2
50	9.6	9.1	8.7	8.3	7.9	7.4	7.0	6.6	6.1	5.7	5.2
60	11.5	11.0	10.2	9.9	9.4	8.9	8.4	7.9	7.3	6.8	6.3
70	13.4	12.8	12.2	11.6	11.0	10.4	9.8	9.2	8.5	7.9	7.3
80	15.3	14.6	13.9	13.2	12.5	11.9	11.2	10.5	9.8	9.0	8.3
90	17.2	16.4	15.6	14.9	14.1	13.3	12.9	11.8	11.0	10.2	9.4
100	19.1	18.2	17.4	16.5	15.7	14.8	14.3	13.1	12.2	11.3	10.4
110	21.0	20.0	19.1	18.2	17.2	16.3	15.3	14.4	13.4	12.4	11.4
120	22.9	21.9	20.8	19.8	18.8	17.8	16.7	15.7	14.6	13.6	12.5
130	24.8	23.7	22.6	21.5	20.4	19.2	18.1	17.0	15.8	14.7	13.5
140	26.7	25.5	24.3	23.1	21.9	20.7	19.5	18.3	17.0	15.8	14.6
150	28.6	27.3	26.0	24.8	23.5	22.2	20.9	19.6	18.3	16.9	15.6

AQL=0.10   PO=0.90

N	L/C 0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10	1.9	1.8	1.7	1.7	1.6	1.5	1.4	1.3	1.2	1.1	1.0
20	3.8	3.7	3.5	3.3	3.1	2.9	2.8	2.6	2.4	2.2	2.0
30	5.7	5.5	5.2	4.9	4.7	4.4	4.1	3.9	3.6	3.4	3.1
40	7.6	7.3	6.9	6.6	6.2	5.8	5.5	5.1	4.8	4.5	4.1
50	9.5	9.1	8.6	8.2	7.8	7.3	6.9	6.4	6.0	5.6	5.1
60	11.3	10.9	10.4	9.8	9.3	8.7	8.2	7.7	7.2	6.7	6.1
70	13.2	12.7	12.1	11.5	10.9	10.2	9.6	9.0	8.4	7.8	7.1
80	15.1	14.5	13.8	13.1	12.4	11.7	11.0	10.3	9.6	8.8	8.1
90	17.1	16.3	15.6	14.8	14.0	13.1	12.4	11.6	10.8	10.0	9.1
100	19.0	18.2	17.3	16.4	15.5	14.6	13.7	12.8	12.0	11.1	10.2
110	20.8	20.0	19.0	18.0	17.1	16.0	15.1	14.1	13.1	12.2	11.2
120	22.8	21.8	20.7	19.7	18.6	17.5	16.5	15.4	14.3	13.3	12.2
130	24.7	23.6	22.5	21.3	20.2	19.0	17.9	16.7	15.5	14.4	13.2
140	26.6	25.4	24.2	22.9	21.7	20.5	19.2	18.0	16.7	15.5	14.2
150	28.5	27.2	25.9	24.6	23.3	21.9	20.6	19.3	17.9	16.6	15.2

56

AQL=0.15   PO=0.60

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10		2.8	2.7	2.7	2.6	2.6	2.5	2.4	2.4	2.3	2.2	2.2
20		5.3	5.2	5.0	4.9	4.8	4.7	4.5	4.4	4.3	4.1	4.0
30		7.8	7.6	7.4	7.2	7.0	6.9	6.7	6.5	6.3	6.0	5.8
40		10.2	10.0	9.8	9.5	9.3	9.0	8.9	8.5	8.2	8.0	7.7
50		12.7	12.5	12.2	11.9	11.5	11.2	11.0	10.6	10.2	9.8	9.5
60		15.2	14.9	14.5	14.2	13.8	13.4	13.2	12.6	12.2	11.8	11.4
70		17.7	17.3	16.9	16.5	16.0	15.6	15.3	14.7	14.2	13.7	13.2
80		20.2	19.8	19.3	18.8	18.3	17.8	17.5	16.8	16.2	15.6	15.1
90		22.7	22.2	21.7	21.1	20.6	20.0	19.7	18.9	18.2	17.5	17.0
100		25.2	24.6	24.0	23.4	22.8	22.4	21.5	20.9	20.2	19.4	18.7
110		27.7	27.1	26.4	25.7	25.1	24.6	23.7	22.9	22.2	21.4	20.7
120		30.2	29.5	28.8	28.1	27.3	26.7	25.9	25.0	24.2	23.4	22.5
130		32.7	31.9	31.2	30.4	29.6	28.9	27.9	27.1	26.2	25.3	24.4
140		35.2	34.4	33.5	32.7	31.8	30.9	30.0	29.1	28.2	27.2	26.2
150		37.7	36.8	35.9	35.0	34.1	33.1	32.2	31.2	30.2	29.1	28.1

AQL=0.15   PO=0.70

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10		2.6	2.5	2.5	2.4	2.3	2.2	2.2	2.1	2.0	1.9	1.8
20		5.0	4.8	4.7	4.6	4.5	4.3	4.1	4.0	3.8	3.7	3.5
30		7.5	7.2	7.0	6.8	6.7	6.4	6.1	5.9	5.7	5.4	5.2
40		9.9	9.6	9.3	9.1	8.9	8.5	8.1	7.8	7.5	7.2	6.6
50		12.3	12.0	11.6	11.3	11.0	10.6	10.1	9.7	9.4	9.0	8.0
60		14.8	14.3	13.9	13.5	13.2	12.7	12.1	11.7	11.2	10.5	9.6
70		17.2	16.7	16.2	15.7	15.4	14.7	14.1	13.5	13.0	12.3	11.3
80		19.6	19.1	18.5	17.9	17.6	16.8	16.1	15.4	14.7	14.3	13.6
90		22.1	21.4	20.8	20.1	19.8	18.9	18.1	17.4	16.6	16.0	15.3
100		24.5	23.8	23.1	22.3	21.9	20.9	20.1	19.4	18.4	17.8	17.0
110		26.9	26.1	25.4	24.6	24.0	22.5	22.1	21.3	20.3	19.6	18.4
120		29.4	28.5	27.7	26.8	25.8	25.0	24.1	23.2	22.3	21.3	20.4
130		31.8	30.9	29.9	29.0	28.0	27.2	26.1	25.1	24.1	23.1	22.0
140		34.2	33.2	32.2	31.2	30.2	29.2	28.1	27.0	25.9	24.8	23.7
150		36.7	35.6	34.5	33.4	32.3	31.2	30.1	29.0	27.8	26.6	25.4

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		2.5	2.4	2.3	2.2	2.2	2.1	2.0	1.9	1.8	1.7	1.7
200		4.9	4.7	4.6	4.4	4.3	4.1	3.9	3.7	3.6	3.4	3.2
300		7.3	7.0	6.8	6.7	6.3	6.1	5.8	5.6	5.3	5.1	4.8
400		9.7	9.3	9.0	8.7	8.5	8.1	7.7	7.4	7.1	6.8	6.4
500		12.1	11.7	11.3	10.9	10.6	10.1	9.7	9.3	8.8	8.4	8.0
600		14.4	14.3	13.5	13.0	12.6	12.1	11.6	11.1	10.6	10.1	9.6
700		16.8	16.6	15.7	15.2	14.6	14.1	13.5	12.9	12.4	11.8	11.2
800		19.2	18.9	18.0	17.4	16.7	16.1	15.4	14.8	14.1	13.5	12.8
900		21.6	20.9	20.2	19.5	18.9	18.1	17.3	16.6	15.9	15.1	14.4
1000		24.0	23.2	22.5	21.7	20.9	20.1	19.2	18.4	17.6	16.8	16.0
1100		26.4	25.6	24.7	23.8	23.0	22.1	21.2	20.3	19.4	18.5	17.6
1200		28.8	27.9	26.9	26.0	25.0	24.1	23.1	22.1	21.1	20.1	19.2
1300		31.6	30.2	29.2	28.1	27.1	26.1	25.0	24.0	22.9	21.8	20.7
1400		33.6	32.5	31.4	30.3	29.2	28.1	26.9	25.8	24.7	23.5	22.3
1500		36.0	34.8	33.7	32.5	31.3	30.1	28.9	27.6	26.4	25.2	23.9

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		2.4	2.3	2.2	2.2	2.1	2.0	1.9	1.8	1.7	1.6	1.6
200		4.8	4.6	4.4	4.3	4.1	3.9	3.8	3.6	3.4	3.3	3.1
300		7.1	6.9	6.6	6.4	6.2	5.8	5.6	5.4	5.1	4.9	4.6
400		9.5	9.2	8.8	8.5	8.2	7.8	7.5	7.2	6.8	6.5	6.2
500		11.9	11.5	11.0	10.6	10.2	9.8	9.4	9.0	8.5	8.1	7.7
600		14.2	13.7	13.2	12.8	12.3	11.7	11.3	10.8	10.2	9.7	9.2
700		16.6	16.0	15.4	14.9	14.3	13.6	13.1	12.5	12.0	11.4	10.8
800		19.0	18.3	17.6	17.0	16.4	15.5	15.0	14.3	13.7	13.0	12.3
900		21.3	20.6	19.9	19.1	18.4	17.6	16.7	16.1	15.1	14.6	13.8
1000		23.7	22.9	22.1	21.2	20.4	19.5	18.6	17.9	17.1	16.2	15.4
1100		26.1	25.2	24.3	23.4	22.4	21.5	20.5	19.7	18.8	17.8	16.9
1200		28.5	27.5	26.5	25.5	24.5	23.4	22.4	21.5	20.5	19.5	18.4
1300		30.8	29.8	28.7	27.6	26.5	25.4	24.4	23.3	22.2	21.1	20.0
1400		33.2	32.0	30.9	29.7	28.6	27.4	26.2	25.1	23.9	22.7	21.5
1500		35.6	34.3	33.1	31.8	30.6	29.3	28.1	26.8	25.6	24.3	23.0

AQL=0.20   P0=0.60

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10	3.6	3.5	3.5	3.4	3.4	3.3	3.3	3.2	3.2	3.1	3.1
20	6.7	6.7	6.6	6.5	6.3	6.2	6.2	6.1	6.0	5.9	5.8
30	9.9	9.7	9.7	9.6	9.3	9.2	9.0	8.9	8.7	8.6	8.4
40	13.2	12.0	12.7	12.5	12.3	12.1	11.9	11.7	11.5	11.3	11.8
50	16.4	16.1	15.8	15.6	15.3	15.0	14.7	14.6	14.3	14.8	13.5
60	19.6	19.1	18.9	18.6	18.3	18.0	17.6	17.4	17.0	16.5	16.2
70	22.6	22.3	21.0	21.6	21.3	20.9	20.5	20.2	19.7	19.3	19.2
80	25.7	25.4	25.0	24.7	24.3	23.8	23.4	23.0	22.5	22.0	21.8
90	28.9	28.5	28.1	27.7	27.2	26.8	26.3	25.9	25.2	25.0	24.5
100	32.3	31.6	31.2	30.7	30.2	29.7	29.1	28.8	28.0	27.5	27.2
110	35.3	34.8	34.3	33.7	33.2	32.7	32.0	31.6	31.8	30.2	29.6
120	38.4	37.9	37.3	36.8	36.2	35.6	35.0	34.4	33.6	33.2	32.3
130	41.6	41.0	40.4	39.9	39.2	38.5	37.9	37.3	36.4	35.9	35.3
140	44.8	44.2	43.5	42.9	42.2	41.4	40.8	40.1	39.4	38.7	37.9
150	48.0	47.3	46.6	45.9	45.2	44.4	43.7	43.0	42.2	41.4	40.6

AQL=0.20   P0=0.70

N	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
10	3.3	3.2	3.1	3.1	3.0	2.9	2.9	2.8	2.7	2.7	2.6
20	6.3	6.1	6.0	5.9	5.8	5.6	5.5	5.4	5.2	5.1	4.9
30	9.3	9.1	8.9	8.7	8.5	8.3	8.1	7.9	7.7	7.5	7.3
40	12.3	12.0	11.7	11.4	11.3	11.0	10.8	10.5	10.2	10.4	12.0
50	15.3	15.0	14.6	14.2	14.1	13.7	13.4	13.1	12.7	12.4	14.6
60	18.3	18.0	17.5	17.0	16.8	16.4	16.0	15.6	15.2	14.8	16.1
70	21.4	20.9	20.5	20.0	19.6	19.1	18.7	18.2	17.7	17.3	19.5
80	24.4	23.8	23.4	22.9	22.4	21.8	21.3	20.8	20.3	19.7	23.9
90	27.4	26.8	26.2	25.5	25.1	24.6	24.0	23.4	22.8	22.6	24.5
100	30.4	29.8	29.2	28.5	27.9	27.3	26.6	25.9	25.3	24.5	28.2
110	33.4	32.7	32.0	31.4	30.7	30.0	29.2	28.5	27.8	27.0	28.6
120	36.5	35.7	35.0	34.2	33.4	32.7	31.9	31.1	30.3	29.5	31.0
130	39.5	38.7	37.8	37.0	36.2	35.4	34.5	33.7	32.8	31.9	34.7
140	42.5	41.6	40.8	39.9	39.0	38.1	37.2	36.2	35.3	34.3	
150	45.5	44.6	43.7	42.7	41.8	40.8	39.8	38.8	37.8	36.8	35.7

AQL=0.20   PO=0.80

N	L/C 0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100	3.0	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.4	2.3	2.2
200	5.9	5.8	5.7	5.5	5.4	5.2	5.1	4.9	4.8	4.6	4.4
300	8.8	8.6	8.4	8.2	8.0	7.8	7.5	7.3	7.1	6.8	6.6
400	11.7	11.5	11.2	10.9	10.6	10.3	10.0	9.7	9.4	9.1	8.8
500	14.7	14.3	14.0	13.6	13.2	12.9	12.5	12.1	11.7	11.3	11.0
600	17.6	17.2	16.7	16.3	15.9	15.4	14.9	14.5	14.1	13.6	13.2
700	20.5	20.0	19.5	19.0	18.5	18.0	17.4	16.9	16.4	15.9	15.5
800	23.4	22.9	22.3	21.7	21.1	20.5	19.9	19.3	18.7	18.1	17.7
900	26.3	25.7	25.0	24.4	23.7	23.1	22.4	21.7	21.1	20.4	19.9
1000	29.2	28.5	27.8	27.1	26.4	25.6	24.8	24.1	23.4	22.6	22.0
1100	32.1	31.4	30.6	29.8	29.0	28.2	27.3	26.5	25.7	24.9	24.2
1200	35.1	34.2	33.4	32.5	31.6	30.7	29.8	29.0	28.0	27.1	26.4
1300	38.0	37.1	36.1	35.2	34.2	33.3	32.3	31.4	30.4	29.4	28.6
1400	40.9	39.9	38.9	37.9	36.9	35.8	34.8	33.8	32.7	31.6	30.6
1500	43.8	42.8	41.7	40.6	39.5	38.4	37.3	36.2	35.0	33.9	32.7

AQL=0.20   PO=0.90

N	L/C 0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100	2.9	2.8	2.7	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1
200	5.7	5.6	5.4	5.3	5.1	5.0	4.8	4.6	4.5	4.3	4.2
300	8.6	8.3	8.1	7.9	7.7	7.4	7.2	6.9	6.7	6.5	6.2
400	11.4	11.1	10.8	10.5	10.2	9.9	9.6	9.2	9.0	8.6	8.3
500	14.3	13.9	13.5	13.1	12.7	12.3	11.9	11.5	11.3	10.8	10.4
600	17.1	16.6	16.2	15.7	15.2	14.8	14.3	13.8	13.6	12.9	12.4
700	19.9	19.4	18.9	18.3	17.8	17.2	16.7	16.1	15.8	15.1	14.5
800	22.8	22.2	21.6	20.9	20.3	19.6	19.1	18.4	18.0	17.2	16.6
900	25.6	24.9	24.2	23.6	22.9	22.1	21.5	20.7	20.3	19.4	18.7
1000	28.5	27.7	26.9	26.2	25.4	24.5	23.8	23.0	22.5	21.5	20.7
1100	31.3	30.5	29.6	28.8	27.9	27.0	26.2	25.3	24.7	23.7	22.8
1200	34.2	33.2	32.3	31.4	30.5	29.4	28.6	27.7	26.9	25.8	24.8
1300	37.0	36.0	35.0	34.0	33.0	31.9	31.0	30.0	28.9	28.0	26.9
1400	39.9	38.8	37.7	36.6	35.5	34.3	33.3	32.3	31.2	30.1	28.9
1500	42.7	41.5	40.4	39.2	38.1	36.8	35.7	34.6	33.4	32.2	31.0

AQL=0.25   PO=0.70

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		4.0	3.9	3.9	3.8	3.8	3.7	3.7	3.6	3.5	3.5	3.4
200		7.6	7.5	7.4	7.3	7.2	7.1	7.0	6.9	6.8	6.7	6.6
300		11.3	11.1	11.0	10.8	10.7	10.5	10.3	10.2	10.3	9.8	9.7
400		14.6	14.7	14.5	14.3	14.6	14.3	13.7	13.8	13.5	13.2	12.8
500		18.6	18.4	18.7	17.8	17.5	17.3	17.1	16.8	16.8	16.4	15.9
600		22.0	22.0	21.7	21.4	21.5	20.7	20.4	20.1	20.1	19.6	19.1
700		26.0	25.6	25.2	24.8	24.5	24.1	23.8	23.4	23.0	22.8	22.2
800		29.6	29.2	28.8	28.4	28.0	27.6	27.2	26.7	26.7	25.8	25.3
900		33.0	32.8	32.4	31.0	31.4	31.0	30.8	30.0	29.2	29.0	28.5
1000		37.0	36.5	35.9	35.9	34.9	34.8	34.2	33.3	32.7	32.4	31.6
1100		40.6	40.1	39.5	38.9	38.4	37.8	37.2	36.6	36.0	35.4	34.7
1200		44.3	43.7	43.1	42.5	41.8	41.2	40.5	39.9	39.2	38.6	37.9
1300		48.0	47.3	46.7	46.0	45.3	44.6	43.9	43.2	42.5	41.7	41.0
1400		51.6	50.9	50.2	49.5	48.8	48.0	47.3	46.5	45.7	44.9	44.1
1500		55.3	54.6	53.8	53.0	52.2	51.4	50.6	49.8	49.0	48.1	47.3

AQL=0.25   PO=0.80

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		3.6	3.6	3.5	3.4	3.4	3.3	3.2	3.2	3.1	3.0	2.9
200		7.1	6.9	6.8	6.7	6.6	6.4	6.3	6.2	6.0	5.8	5.7
300		10.5	10.3	10.2	10.0	9.8	9.6	9.4	9.2	9.0	8.6	8.5
400		14.0	13.8	13.5	13.5	13.2	12.8	12.5	12.2	11.8	11.5	11.3
500		17.5	17.2	16.8	16.8	16.4	15.8	15.6	15.2	14.8	14.5	14.2
600		20.9	20.6	20.3	20.1	19.4	19.1	18.7	18.2	17.7	17.2	17.0
700		24.4	24.0	23.6	23.1	22.8	22.3	21.7	21.2	20.7	20.1	19.8
800		27.9	27.4	26.8	26.9	25.8	25.4	24.8	24.2	23.6	23.0	22.6
900		31.3	30.8	30.2	29.9	29.2	28.6	27.8	27.2	26.5	26.9	25.4
1000		34.8	34.2	33.5	33.4	32.2	31.7	30.9	30.2	29.4	28.7	28.2
1100		38.3	37.6	36.9	36.4	35.8	34.8	34.0	33.2	32.5	31.7	31.8
1200		41.7	41.0	40.2	39.4	38.6	37.8	37.0	36.2	35.4	34.5	36.6
1300		45.2	44.4	43.5	42.7	41.8	41.0	40.1	39.2	38.4	37.5	39.4
1400		48.7	47.8	46.9	46.0	45.1	44.1	43.2	42.3	41.3	40.4	42.2
1500		52.1	51.2	50.2	49.2	48.3	47.3	46.3	45.3	44.3	43.2	

AQL=0.25   PO=0.90

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		3.4	3.3	3.2	3.2	3.1	3.0	3.0	2.9	2.8	2.7	2.7
200		6.7	6.6	6.4	6.3	6.1	6.0	5.8	5.7	5.6	5.4	5.3
300		10.1	9.8	9.6	9.4	9.2	9.0	8.7	8.5	8.3	8.1	7.9
400		13.4	13.1	12.8	12.5	12.2	11.9	11.6	11.4	11.1	10.8	10.5
500		16.7	16.4	16.0	15.6	15.3	14.9	14.5	14.2	13.8	13.5	13.1
600		20.1	19.6	19.2	18.8	18.4	17.9	17.4	17.0	16.6	16.2	15.7
700		23.4	22.9	22.4	21.9	21.4	20.8	20.3	19.9	19.3	18.8	18.3
800		26.7	26.1	25.6	25.0	24.5	23.8	23.2	22.7	22.1	21.5	20.9
900		30.1	29.4	28.8	28.1	27.5	26.8	26.1	25.5	24.6	24.2	23.5
1000		33.4	32.7	32.0	31.2	30.6	29.8	29.0	28.3	27.6	26.9	26.2
1100		36.7	35.9	35.1	34.5	33.6	32.7	32.0	31.2	30.1	29.6	28.8
1200		40.1	39.2	38.3	37.6	36.7	35.7	34.9	34.0	33.1	32.3	31.4
1300		43.4	42.5	41.5	40.6	39.7	38.7	37.8	36.8	35.9	34.9	34.0
1400		46.7	45.7	44.7	43.7	42.7	41.7	40.7	39.7	38.6	37.6	36.6
1500		50.1	49.0	47.9	46.8	45.8	44.7	43.6	42.5	41.4	40.3	39.2

AQL=0.30   PO=0.80

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		4.2	4.2	4.1	4.1	4.0	4.0	3.9	3.9	3.8	3.7	3.7
200		8.3	8.2	8.1	8.0	7.9	7.5	7.6	7.5	7.4	7.3	7.2
300		12.4	12.2	12.0	11.9	11.7	11.3	11.3	11.2	11.0	10.8	10.6
400		16.5	16.2	16.0	15.8	15.4	15.3	15.8	14.8	14.2	14.4	14.1
500		20.5	20.2	19.9	19.6	19.2	19.0	18.5	18.5	18.4	17.9	17.6
600		24.6	24.2	23.9	23.4	23.2	22.6	22.2	22.2	21.8	21.4	21.1
700		28.6	28.2	27.8	27.4	27.0	26.4	26.2	25.8	25.4	25.0	24.6
800		32.7	32.2	31.7	31.2	30.9	30.4	30.0	29.5	29.0	28.5	28.1
900		36.7	36.2	35.7	35.1	34.7	34.2	37.4	33.2	32.6	32.6	31.5
1000		40.8	40.3	39.7	39.0	38.6	38.0	37.4	36.8	36.2	35.6	35.0
1100		44.9	44.3	43.6	43.0	42.2	41.8	41.8	40.5	39.8	39.2	38.0
1200		48.9	48.3	47.6	46.8	46.2	45.5	44.8	44.1	43.4	42.7	42.0
1300		53.0	52.3	51.5	50.7	50.1	49.3	48.6	47.8	47.0	46.3	45.5
1400		57.1	56.3	55.5	54.7	53.8	53.1	52.3	51.5	50.7	49.8	49.0
1500		61.1	60.3	59.5	58.6	57.8	56.9	56.0	55.1	54.3	53.4	52.5

AQL=0.30   PO=0.90

N	L/C	0.90	0.91	0.92	0.93	0.94	0.95	0.96	0.97	0.98	0.99	1.00
100		3.9	3.8	3.8	3.7	3.6	3.6	3.5	3.4	3.4	3.3	3.2
200		7.7	7.6	7.5	7.3	7.2	7.1	6.9	6.8	6.7	6.5	6.4
300		11.6	11.4	11.2	11.0	10.8	10.6	10.4	10.2	10.3	13.0	9.6
400		15.4	15.2	14.9	14.6	14.5	14.1	13.8	13.6	13.6	13.5	12.9
500		19.2	18.7	18.6	18.3	17.5	17.6	17.3	16.9	16.9	16.7	15.9
600		23.1	22.5	22.3	21.9	21.5	21.1	20.7	20.3	19.8	19.2	19.3
700		26.8	26.5	26.0	25.5	25.1	24.6	24.2	23.7	23.5	22.5	22.6
800		30.8	30.2	29.7	29.2	28.2	28.1	27.5	27.1	26.8	26.2	25.8
900		34.6	34.0	33.4	32.8	32.2	31.6	31.0	30.4	29.8	29.2	28.8
1000		38.4	37.8	37.1	36.5	35.8	35.2	34.5	33.8	33.4	32.7	32.0
1100		42.3	41.5	40.8	40.1	39.4	38.7	37.9	37.2	36.4	35.7	35.1
1200		46.1	45.3	44.5	43.7	43.0	42.2	41.4	40.6	39.8	38.2	38.3
1300		49.9	49.1	48.2	47.4	46.5	45.7	44.8	43.9	43.1	42.2	41.3
1400		53.8	52.9	51.9	51.0	50.1	49.2	48.2	47.3	46.4	45.4	44.5
1500		57.6	56.6	55.7	54.7	53.7	52.7	51.7	50.7	49.7	48.7	47.7

LIST OF REFERENCES

1. Brown, G. G., and Rutemiller, H. C., "Tables for Determining Expected Cost Per Unit Under MIL-STD-105D Single Sampling Schemes," AIIE Transactions, V. 6, pp. 135-142, June 1974.

2. Duncan, A. J., Quality Control and Industrial Statistics, 4th Ed., p. 165, Irwin, 1974.

3. Flehinger, B. J., and Miller, J., "Incentive Contracts and Price Differential Acceptance Tests," Journal of the American Statistical Association, V. 59, pp. 149-159, March 1964.

4. Foster, J. W., "Price Adjusted Sampling Plan," International Journal of Production Research, V. 8, 1970.

5. Foster, J. W., and Perry, O. T., "Price Adjusted Single Sampling with Linear Indifference," Journal of Quality Technology, V. 4, pp. 134-144, July 1972.

6. Foster, J. W., and Perry, O. T., "Price Adjusted Single Sampling with Quadratic Indifference," AIIE Transactions, V. 9, pp. 88-94, March 1977.

7. Officer of the Chief of Ordnance, ORDP 20-1, Tables of the Cumulative Binomial Probabilities, 1952.

8. Office of Management and Budget, Circular No. A-76, Policies for Acquiring Commercial or Industrial Products and Services Needed by the Government, March 1979.

9. Roeloffs, R., "Acceptance Sampling Plans with Price Differentials," The Journal of Industrial Engineering, V. 18, pp. 96-100, January 1967.

INITIAL DISTRIBUTION LIST

		No. Copies
1.	Defense Technical Information Center Cameron Station Alexandria, Virginia 22314	2
2.	Library, Code 0142 Naval Postgraduate School Monterey, California 93940	2
3.	Department Chairman, Code 55 Department of Operations Research Naval Postgraduate School Monterey, California 93940	1
4.	Assoc. Prof. G. Lindsay, Code 55Ls Department of Operations Research Naval Postgraduate School Monterey, California 93940	1
5.	LCDR James P. Kovalcik, CEC, USN Naval Facilities Engineering Command 200 Stovall Street Alexandria, Virginia 22314	1
6.	LT William P. Keane, CEC, USN NAVDAC, Code 53 Washington Navy Yard Washington, DC 20374	1
7.	LT Dennis Lee, CEC, USN Civil Engineer Corps Officers School Construction Battalion Center Port Hueneme, California 93041	1